

29. 28.
32. 33.

2214.10'
2" iron TRUE SECTOR
12" dia. 1/4" of Road
See Ties
N.P. 15" N 34° 25' E 63.8 Ft
N.P. 16" N 63° 10' W 61.8 "
N.P. 14" S 32° 40' W 79.5 "
R.OOK 16'S 69" E 102.7 "
To Spot of base - Nor 1' 30" E Magnet
course turned FROM TRUE SECLINE
WHICH RUNS S 22° 57' E

Certificate of County Surveyor

I, John W. Cura hereby certify that I have very carefully and very accurately surveyed the true section line bet sections 32 and 33 Twp 44 N R 28 W Cass Co. Minn. That the section corners at each end of this line, are, of the true points established in the original U.S. survey and this plat accurately represents my survey.

Survey finished April 26-1942.
This plat: Dated at Walker, Minnesota April 29-1942.

NORTH
VOR 6° 30'

Scale: 1 Inch = 400 Feet
Iron Monuments

OK.
Cura

Sec 32.
T141 R 28.

Sec 33.
T141 R 28.

This survey recorded in my office this 29th day of April A.D. 1942 on page 284 to 289 in County Record Book "D" of Surveys Cass Co Minn.

John W. Cura
Minn Reg No 1428
Seol.
County Surveyor
Cass Co. Minn

10th Standard Parallel
True East and West. Straight line
2 Miles U.S. ch. To Twp Cor

10560 Ft. U.S. chain = 10520 Ft. My chain
= 40. Ft. Short in 2 miles

TRUE COR SECS 32-33-141-28
T.M. TIES VIZ:
4" W. OOK N 47° 45' W 90.10 Ft
7" Basswood N 24° 15' E 68.40 Ft

29. 28.

32. 33.

2214.10'
2" Iron True Sec cor
12 ft N of 4 of Road
see Ties:

NR. 15" N 34° 25' E 63.8 ft
 NP 14" N 63° 10' W 61.8 "
 NP 14" S 32° 40' W 79.5 "
 R. Oak 16' 07" E 102.7 "
 To Spot of base - Vor 6° 30' E Magnet
 course turned from True Sec line
 which runs S 22° 57' E

Certificate of County Surveyor

I, John W. Curro hereby certify that I have very carefully and very accurately surveyed the True Section line bet sections 32 and 33 Twp 141 N R 28 W Cass Co. Minn. That the Section Corners of each end of this line, one of the true points established in the original U.S. Survey and this plat accurately represents my survey.

Survey finished April 26, 1942.

This plat: Dated at Walker, Minnesota April 29, 1942.

N.
VOR 6° 30'

Scale: Linch = 400 Feet
 O = Iron Monuments

Sec 32.
T141 R 28

Sec 33.
T141 R 28

Gov Lot 5
Sec 33
Most all
in lake

This survey recorded in my office this 29th day of April A.D. 1942 on page 286 To 289 in County Record Book "D" of surveys Cass Co Minn.

John W. Curro
 Minn Reg No 1428
 Seal
 County Surveyor
 Cass Co. Minn

10th Standard Parallel
 True East and west Straight line
 2 Miles U.S. ch. to Twp cor

10.5607 U.S. chain 10.5201 Mch chain
 = 40 ft short in 2 miles

True cor 3 Secs 32-33 14-28
 3rd ties via:
 4" W Oak N 47° 43' W 90.10 ft
 7" Basswood N 24° 15' E 68.40 ft

726 Ft 5 4

#5874