CERTIFICATE OF	LOCATION	OF GC	VERNMEN	NT CORNER
Standard Quarter Corner to Sec33	<i>T</i> . 145	N	R. 26W	
State of Minnesota,				
County of Cass				
I hereby certify that on the	16th	day ofMa	ırch	1971
found the Standard Quarter	corner of Section	n 33		
which was evidenced byremains c Service record	f R. W. Fassett	resurveyc	of1953anddoc	eumented in Forest
and I further certify that to perpeti	iate the location of	such corner	I did, at the exc	nct location thereof, place
permanent marker consisting of	2 inch x 60 i	nchgalvani	zedsteelpip	e_with_brass_cap
I further certify that I establish	red			
reference or witness monuments cons	isting of			
which reference or witness monument	ts are located in the	e manner foll	owing:	
Tamarack 12 inch N67 E 27.10	feet scribed SC	± S33 BT		
Ash 6 inch N28 ⁰ W 47.40 feet s				
Tamarack 14 inch N73 W 3.30 f	eet scribed SC	뷰 S33 BT		
Dated at CASS LAME	, Minn., th	is 28 TH	day of	NOVEMBER 1978
246278 office of register of deeds	MICROFILM		MILO E.	STEFAN
County of Coss	}	Min	nesota Kegiste	red Surveyor No. 12261
I hereby certify that the with	in instrument was	filed in this	office for record	on the 14
day of June	A. D. 19.7.9	at 2:40	o'clock	P. M.
U		Benlah	. Herdink	Rounly & County Recor