CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
CN 1/16 Corner of Section 2 ,Township 141 ,Range 30 , 5 P.M.  STATE OF MINNESOTA, County of CASS	
At the corner location shown on the sketch:	
On 10-23-81 found a 1"x36" brass cap monument standing in good condition with one original BT standing green  □ left monument as found, □ lowered monument, □ removed monument (explain)	
□ On placed a	
OATE PIUCEG U	
SKETCH OF REFERENCE TIES	
1 4	
-N- 	
14" RED OAK ORIGINAL B.T.	
N.So.M	
SIGN WEST	
3101V 2.77 S62°F	
3460 53 17 18	
SIGN S' RED OAK	
548° W 9" RED OAK	
8"RED OAK	
	7" TRIPLE MAPLE
not to scale	
Statement of evidence relative to this corner location is on back of page.	
I hereby certify that this document and the data OFFICE OF THE REGISTER OF DEEDS	
contained herein was prepared by me or under	County of
my direct supervision.	I hereby certify that this document was filed in the Reg. of Deeds office at 11:15 A.M. on the
SIGNATURE DATE	
Registration No. 11395	Register of Deeds Deulah Herbuch
A Land Surveyor, □ Professional Engineer	DOCUMENT NO. 262613
☐ County Surveyor, ☐ County Engineer	DOCUMENT NO

In 1917, Earl G. Harrington, a US surveyor set a 1"x36" iron pipe with brass cap for the CN 1/16 corner from which he made the following BT's: A 12" poplar S  $30\frac{1}{2}$  E 11 LKS and a 10" red oak N  $72\frac{1}{2}$  W 46 LKS.

On October 23, 1981, Walter Curo and Paul Johnson find the brass cap monument standing in good condition. A 14" red oak sets N 72 W 30.3 feet. The other BT is gone. We make new BT's as shown on front.