CERTIFICATE OF LOCATION OF GOVERNMENT CORNER			
AP 3 TR 1664 Corner of Section 11 , Township 141 , Range 30 , 5 P.M.			
STATE OF MINNESOTA, County of			
		☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
		Onplaced a	
SKETCH OF REFERENCE TIES			
A SKETOTI OF KEI EKEKSE TIES			
7" WHITE OAK			
-N-			
4" WHITE OAK			
SIGN 66.87			
The state of the s			
6" RED OAK NB2°W N60 II.37' EAST SIGN			
2.9'			
not to scale			
Statement of evidence relative to this corner location is on back of page.			
I hereby certify that this document and the data	26 2639 OFFICE OF THE REGISTER OF DEEDS		
contained herein was prepared by me or under	County of <u>law</u>		
my direct supervision.	I hereby certify that this document was filed in the Reg. of Deeds office at $\frac{2.2.5}{\rho}$. M. on the		
SIGNATURE 12-8-8/	7 day of May A.D., 1982		
Registration No. 11395	Register of Deeds Bulah Herdunh By M. S. ,Deputy		
☐ Land Surveyor, ☐ Professional Engineer ☐ County Surveyor, ☐ County Engineer	DOCUMENT NO. 2629		

In 1917, Earl G. Harrington, a US surveyor set a 1"x36" iron pipe with brass cap for AP 3 TR 1664 and AP 4 TR 1663. No Bt's were made.

On October 27, 1981, Walter Curo and Paul Johnson find the brass cap monument standing in good condition from which we make BT's as shown on the front.