CERTIFICATE OF LOCATION OF GOVERNMENT CORNER  East Quarter			
		At the corner location shown on the sketch:	
		On 12/27/82 found o 2" capped pipe.	
☑ left monument as found, □ lowered monument, □ removed monument (explain)			
□ Onplaced a			
SKETCH OF REFERENCE TIES			
· <b>/</b>			
4			
- N-	Copper nail & disk		
	In 5" Burr Oak		
Copper nail & disk In 6" Burr Oak up 3!	38.50' N25°E		
N25°W 29.60'	7		
	/		
Copper nail & disk In 5" Maple up 3'	*		
N70°W 17.24'	East 81,80		
	Copper nail & disk		
	In 24" White Pine up 3"		
	Schneider BT		
SECTION 6	SECTION 5		
	Bearings are magnetic.		
	,		
·····			
Statement of evidence relative to this corner location is on back of page.			
	267919		
I hereby certify that this document and the data	OFFICE OF THE COUNTY RECORDER		
contained herein was prepared by me or under	County of Can		
my direct supervision.	I hereby certify that this document was filed in		
	the Co. Recorders office at 9.25 A.M. on the		
James W. Nielsen 3/4/83 SIGNATURE DATE	4 day of April A.D., 198-		
Registration No. 11865	County Recorder Claudine Kaylon		
☑ Land Surveyor, ☐ Professional Engineer	County Recorder Claudine Kaylan  By MS  Deputy		
☐ County Surveyor, ☐ County Engineer	DOCUMENT NO. 26 7919		
- Journ's July Cycli, - Journ's Eligineer			

Mn/DOT 2105 (4-77)

Statement of Evidence: East Quarter Corner of Section 6, Township 140 North, Range 30 West, 5th Principal Meridian

The Original Public Land Survey was run in 1865 and a wood post was set to mark the corner.

In 1923 Mr. John Greene, County Surveyor, set a 2" capped pipe at a lost porportion position.

In 1966 Mr. R. Schneider found the 2" capped pipe and made two bearing tree ties.

In 1982 the Minnesota Department of Transportation recovered the 2" capped pipe and one of Mr. Schneider's bearing trees, and accept this as the correct location for the corner.

For details and survey analysis contact the Minnesota Department of Transportation District Surveys Office in Brainerd, Minnesota.