

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

SOUTHEAST SIXTEENTH Corner of Section 18, Township 141, Range 27, 5th P.M.

STATE OF MINNESOTA, County of CASS



At the corner location shown on the sketch:

On 10/15/80 found a GLO brass cap monument as set in 1919.
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES



BEARINGS ARE APPROXIMATE

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Nancy H. Stevenson 9-14-82
SIGNATURE DATE

Registration No. 12684

- Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

279235
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 9:50 A.M. on the 5 day of Dec. A.D., 1984

County Recorder Clondine Kayler

By MS, Deputy

DOCUMENT NO. 279235

Statement of Evidence:

- 1919 U.S. General Land Office dependent resurvey established this corner and an iron pipe with a marked brass cap was set to mark the corner. The following bearing trees were marked: 10" W. Oak S 30-45 E 179 links and 12" Poplar S 87 E 141 links.
- 1980 U.S. Forest Service technician G. Brama found the corner monumented with a GLO brass cap monument in good condition up 6". The following bearing trees were found: 20" W. Oak S 30 E 118.6'. No evidence found of the Poplar. Two new bearing trees were marked and are shown on this certificate.
- 1982 County Surveyor's Records in the Recorder's Office were checked and no resurvey information was found on this corner.
- 1982 Analysis of the above data indicates that the location of this Government corner has been perpetuated. I accepted the monument as marking the corner location as when set in 1919 by the GLO resurvey based on bearing tree evidence.