CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
	,Township,Range31W,_5thP.M.
STATE OF MINNESOTA, County ofCass	
At the corner location shown on the sketch:	
To On found a	
On found a	
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
On 11-12-84 placed a 2½ inch (0,D,) x 5 foot long iron pipe with a 3 inch diameter brass cap, stamped as shown, up 1.0 foot.	
Declination: 6° East SKETCH OF REFERENCE TIES	
NOT TO	O SCALE
N41°W, 96.70 feet *(1962)	
-N- ``	Red Oak 9 inch
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	N53°E, 66.37 feegむっ
2 from about 1 control 1 c	
Tan	8 foot steel post with F.S. signs 54-9 & 54-2 attached,
S4 S3 East 2.98 feet S9 S10	
White Pine 24 inch S86°W, 57,40 feet	
8 foot steel post with F.S. signs 54-9 & 54-2 attached,	
South 4.50 feet	(1962) Red Oak 10 inch
	Red Oak 16 inch S50°E, 39.21 feet
	S6°E, 18,20 feet
NOTE: All bearing trees are painted red and marked with F.S. sign No. 54-3 with a nail in base, double blazed and scribed.	
Statement of evidence relative to this corner location is on back of page.	
I hereby certify that this document and the data	280558 OFFICE OF COUNTY RECORDER
contained herein was prepared by me or under	County of
my direct supervision.	I hereby certify that this document was filed in
11/10/12 1 Plane 1 >-1-85	the Co. Recorder's office at $9.30 A$.M. on the
SIGNATURE CATE Decidant Alexandre 6807	27 day of february A.D., 1985
Registration No.	County Recorder Clander Koylar
☑ Land Surveyor, □ Professional Engineer	By MS, Deputy DOCUMENT NO. 280558
☐ County Surveyor, ☐ County Engineer	DOCUMENT NO. 280538

Statement of Evidence: Northeast Corner of Section 9, Township 141 North, Range 31 West, 5th Principal Meridian.

1873 P.H. Conger, U.S. Deputy Surveyor, set a post for this Section corner in his subdivision of the Township between August 5, 1873 and August 30, 1873. As references he scribed:

Norway Pine 18 inch N49°E 23 links (15.18 feet) 24 inch Norway Pine N61°W 56 links (36.96 feet) Norway Pine 24 inch S46°W 50 links (33.0 feet S42°E Norway Pine 18 inch 64 links (42.24 feet)

- 1924 J. Greene, Cass County Surveyor, set an iron pipe to perpetuate this corner in his survey of Section 4.
- Peter J. Meyer, R.L.S. with U.S.F.S. found evidence of original BT's. There was no evidence of the iron pipe Greene had set in 1924. A $2\frac{1}{2}$ inch (0.D.) x 5 foot long iron pipe with a 3 inch diameter brass cap was set to perpetuate corner and references made as follows:

Red Pine 16 inch N41°W 96.7 feet
Jack Pine 14 inch N69°E 100.7 feet
Oak 14 inch S6°E 18.2 feet
6 ft steel post East 2.0 feet

Kelly M. Booge, under F.S. Contract No. 53-6392-4-00996, made a thorough search for physical evidence of this corner on August 30 and found the 1962 monument lying down with cap broke off. He found Northwest and Southeast BT's from 1962 in good condition. The Northeast BT is now a 5 foot high stub. He returned November 12 and reset a monument for the corner from remaining BT's and added additional references as shown on the sketch. This Certificate was made to update the 1963 Certificate, Document No. 158, in book of Corner Certificates in Cass County Recorder's Office.

Kelly M. Booge is an employee of Okerman Surveying Inc.