CERTIFICATE OF LOCATION OF GOVERNMENT CORNER North Quarter Corner of Section 22 Township 144 N., Range 25 W., 5th P.M.	
STATE OF MINNESOTA, County of Cass	
At the corner location shown on the sketch:	
On found a	
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
On 1-3-1985 placed a 5/8"by 5 feet long Aluminum Rod with 3"Aluminum Csp stamped as shown, up 0.50 feet.	
	EFERENCE TIES
4	, SCACE
6" Tamara	ck
1,80000	
1/4	144N R25W 5 15 5 22 1985 RLS 9235
(((1))) 5.70°00'00''E.	
NOTE: Trees are Blazed and Scribed with B.T. Tags. Distances shown are to a 20 ^d Nail in Notch painted red on side of Tree.	
Statement of evidence relative to this corner location is on back of page.	
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision. 3/23/85 SIGNATURE 3/23/85 Registration No. 9235	OFFICE OF THE COUNTY RECORDER County of
☐ County Surveyor, ☐ County Engineer	DOCUMENT NO. 28/808

Statement of Evidence:

N15

This corner was originally established in April; 1876, by B.C. Baldwin, Deputy Surveyor. The field notes of that survey are filed in the office of the Secretary of State, St. Paul, Minnesota. Mr. Baldwin's notes state that a post was set to mark the corner and referenced by the following:

A 6" Tamarack that bears N9°W a distance of 10 links [6.60 feet]
A 5" Tamarack that bears S15°E a distance of 13 links [8.58 feet]

On July 6, 1984, personnel from Advance Surveying & Engineering Co. made a thorough search for this corner and the above mentioned references but to no avail. This search area is Cedar, Tamarack and Spruce swamp.

On January 3, 1985, an additional search was made by Advance prior to reestablishing this corner at its "lost" position half way and on line between adjacent section corners and as shown on the sketch.