

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 23, Township 144 N., Range 25 W., 5th P.M.


STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

- On _____ found a _____
DATE
- left monument as found, lowered monument, removed monument (explain)
- On 1-29-1985 placed a 5/8" by 8 feet long Aluminum Rod with 3" Aluminum Cap
DATE stamped as shown, up 1.00 foot.

5° EAST Declination

SKETCH OF REFERENCE TIES
NOT TO SCALE



NOTE: Trees are Blazed and Scribed with B. T. Tags. Distances shown are to a 20^d Nail in Notch painted red on side of Tree.

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

James H. Parker 3/29/85
SIGNATURE DATE

Registration No. 9235

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

281953
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 9:40 A.M. on the 15 day of May A.D., 1985

County Recorder Claudia Kayler

By ms, Deputy

DOCUMENT NO. 281953

Statement of Evidence:

P21

This corner was originally established in April, 1876, by B.C. Baldwin, Deputy Surveyor. The field notes of that survey are filed in the office of the Secretary of State, St. Paul, Minnesota. Mr. Baldwin's notes state that a post was set to mark the corner and referenced by the following:

A 3" Tamarack that bears S87°E a distance of 7 links [4.62 feet]
A 4" Tamarack that bears S12°W a distance of 62 links [40.92 feet]

In 1900, A Map of survey by the Corps of Engineers shows that they found the corner.

On July 31, 1984, personnel from Advance Surveying & Engineering Co. made a thorough search for this corner and the above mentioned references but to no avail. This area is all Tamarack swamp, with trees approximately 3" to 5" diameter.

On January 29, 1985, an additional search was made by Advance prior to reestablishing this corner by Obliterated methods by using coordinate position determined from Corps of Engineers Survey done in 1900.