

C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the North Quarter Corner of Section 17, Township 141 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On July 2, 1985, to mark this corner position, we set a 2.5 inch (outside diameter) by 24 inch long galvanized iron pipe with a 3 inch diameter brass tablet, 12 inches below the road surface, and stamped as shown in the sketch.


SKETCH OF REFERENCE TIES

decl: 5° E

(not to scale)

Top of page is NORTH

N 27° W, 91.68 feet to a 16d nail  
in the southwesterly face  
of a 7.1 inch diameter  
Ash, double blazed and  
scribed "1/4 S8" and "BT".



C.S.A.H. No. 132

S 39° W, 72.34 feet to  
a 16d nail in the southeasterly  
face of a 9.2 inch diameter Ash,  
double blazed and scribed "1/4 S17"  
and "BT".



S 16° E, 53.20 feet  
to a 16d nail in the westerly  
face of a 13.6 inch diameter  
Balsam Poplar, double blazed  
and scribed "1/4 S17" and  
"BT".



All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*

Kenneth L. Whitehorn

Date 9-26-85 Registration No. 14677

285564  
OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 19 85, at 9:55 A.M. and assigned DOCUMENT NUMBER 285564.

*Claudia Kayler*  
County Recorder

MS

STATEMENT OF EVIDENCE: North Quarter Corner of Section 17, Township 141 North, Range 25 West, of the 5th Principal Meridian.

This corner was originally established by Edgar P. Putman and William P. Allen, Deputy Surveyors, in April of 1871. The record of that survey is on file in the Office of the Secretary of State, St. Paul, Minnesota. Their notes indicate that a post was set to mark the corner and referenced by: an 8 inch diameter Tamarack that bears SOUTH 25 degrees WEST, a distance of 20 links (13.20 feet); and a 7 inch diameter Tamarack that bears NORTH 42 degrees WEST, a distance of 14 links (9.24 feet).

In 1913, J. H. Flynn, Cass County Surveyor, found both of the old government bearing trees. He then established: a 9 inch diameter Tamarack that bears SOUTH 16 degrees WEST, a distance of 23.5 feet; and a 6 inch diameter Fir that bears NORTH 17 degrees WEST, a distance of 23.8 feet. This information was found in Book "C", SURVEYOR'S RECORD, Office of the Cass County Recorder, Walker, Minnesota.

On May 27, 1920, while traversing around Section 17, John Curo, R.L.S., found a 4 inch square wood post drove down into the intersection of the Remer and Shovel Lake roads. The post was scribed "1/4 S". No mention of the 1913 bearing trees were made. This information was found in his field notes, Hackensack, Minnesota.

John Curo returned to this corner on June 5, 1920, and pulled out the wood post and replaced it with a 4 foot long by 2 inch diameter iron pipe, driven down 4 feet into the middle of the Shovel Lake road. This information was found in his field notes, Hackensack, Minnesota.

On June 17, 1985, a 2.5 inch (outside diameter) bent over iron pipe was found laying in a nearby ditch. We then dug a 4 foot diameter hole at the centerline intersection of the old Remer and Shovel Lake roads, but no evidence was recovered. This road intersection was tied into our EDM / theodolite traverse.. That shows this position agrees very well with the 1913 Cass County survey.

Based on the traverse between the recovered Northwest and Northeast Corners of Section 17, I feel that the centerline intersection of the existing Shovel Lake Road and the remaining evidence of the Remer Road is the best remaining evidence of the original position. A Forest Service survey crew returned to this area on July 2, 1985, to perpetuate this corner position and set the monument and new witnesses as shown on the sketch. The records of this survey are on file with the USDA Forest Service, Chippewa National Forest.