


C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the North Quarter Corner of Section 16, Township 141 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On July 2, 1985, to mark this corner position, we set a 2.5 inch (outside diameter) by 24 inch long galvanized iron pipe with a 3 inch diameter brass tablet, 8 inches below the the road surface, and stamped as shown below.


SKETCH OF REFERENCE TIES
(not to scale)

decl: 5° E



N 16° W, 56.83 feet to a 16d nail in the southwesterly face of a 11.0 inch diameter Red Pine, double blazed and scribed "1/4 S9" and "BT".

N 16° E, 69.80 feet to a 16d nail in the easterly face of a 12.5 inch diameter Aspen, double blazed and scribed "1/4 S9" and "BT".



C. S. A. H. No. 132

S 22° E, 33.95 feet to a 16d nail in the southwesterly face of a 12.4 inch diameter White Oak, double blazed and scribed "1/4 S16" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date 9-24-85 Registration No. 14677

²⁸⁵⁵⁶⁶
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 1985, at 9:15 A.M. and assigned DOCUMENT NUMBER 285566.

Claudia Kayler
County Recorder
M)

STATEMENT OF EVIDENCE: North Quarter Corner of Section 16, Township 141 North, Range 25 West, of the 5th Principal Meridian.

This corner was originally established by Edgar P. Putman and William P. Allen, Deputy Surveyors, in April of 1871. The record of that survey is on file in the Office of the Secretary of State, St. Paul, Minnesota. Their notes indicate that a post was set to mark the corner and referenced by: an 8 inch diameter Fir that bears NORTH 59 degrees EAST, a distance of 28 links (18.48 feet); and a 10 inch diameter Elm that bears SOUTH 20 degrees WEST, a distance of 17 links (11.22 feet).

In 1913, J. H. Flynn, Cass County Surveyor, recovered a stub of the Elm bearing tree and part of a down Fir. He then established a 24 inch diameter White Pine stump that bears SOUTH 22 degrees 30 minutes WEST, a distance of 35.0 feet. This information was found in Book "C", page 37, SURVEYOR'S RECORD, Office of the Cass County Recorder, Walker, Minnesota.

In the Supervisor's Office, Chippewa National Forest, Cass Lake, Minnesota, is a Forest Service form 874-9 by R. DeFant dated July 2, 1940. It states that the corner consists of a post in fair condition, 12 inches above the ground. From this post stands a 24 inch diameter stump that bears SOUTH 45 degrees WEST, a distance of 52 links (34.32 feet), with the scribing "1/4 S16 BT". He then put a Metal Location Poster on the same stump.

On June 18, 1985, a Forest Service survey crew found the 1913 White Pine stump which was badly decayed. The record bearing and distance from the stump falls in the centerline of the Shovel Lake Road (C.S.A.H. 132). A hole 2 feet in diameter and 1.5 feet deep was dug but no further evidence was found. An EDM/theodolite traverse was run from this point to the Northeast Corner of Section 17 and found the distance to be within 1.5 feet of the distance given in the 1913 survey.

I feel this stump is the remains of the 1913 Flynn Survey and a perpetuation of the original corner position. A Forest Service survey crew returned to the area on July 2, 1985, and set the monument and references as shown on the sketch. The records of this survey are on file with the USDA Forest Service, Chippewa National Forest.