

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the East Quarter Corner of Section 16, Township 141 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.


On August 1, 1985, to mark this corner position, we set a 2.5 inch (outside diameter) by 24 inch long aluminum pipe with a 3 inch diameter domed aluminum cap, 6 inches below the road surface, and stamped as shown.

SKETCH OF REFERENCE TIES
(not to scale)
Top of page is NORTH

decl: 5° E

N 30° W, 15.91 feet to the face of an 8 foot long metal post.

Old Road



S 83° E, 10.61 feet to the face of an 8 foot long metal post.

S 55° W, 10.89 feet to the face of an 8 foot long metal post.

All metal fence posts are marked with red enamel and a USFS 54-3 "BEARING TREE TAG".

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date 9-24-85 Registration No. 14677

²⁸⁵⁵⁶⁹
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 1985, at 9:30 A.M. and assigned DOCUMENT NUMBER 285569.

Claudine Kayler
County Recorder

ms

STATEMENT OF EVIDENCE: East Quarter Corner of Section 16, Township 141 North,
Range 25 West, of the 5th Principal Meridian.

This corner was originally established by Edgar P. Putman and William P. Allen, Deputy Surveyors, in April of 1871. The record of that survey is on file in the Office of the Secretary of State, St. Paul, Minnesota. Their notes indicate that a post was set to mark the corner and referenced by: an 8 inch diameter Tamarack that bears NORTH 50 degrees EAST, a distance of 12 links (7.92 feet); and a 10 inch diameter Tamarack that bears NORTH 54 degrees WEST, a distance of 18 link (11.88 feet).

In 1913, J. H. Flynn, Cass County Surveyor, recovered the old government bearing trees: an 8 inch diameter Tamarack stump that bears NORTH 50 degrees EAST, a distance of 12 links (7.92 feet); and a 10 inch diameter Tamarack stump that bears NORTH 54 degrees WEST, a distance of 18 links (11.88 feet). He then established: a 6 inch diameter Cedar that bears NORTH 63 degrees WEST, a distance of 35.6 feet; and a 7 inch diameter Spruce that bears NORTH 82 degrees EAST, a distance of 37.1 feet. This information can be found in the Cass County Survey Records, book "C", page 37.

In the Supervisor's Office, Chippewa National Forest, Cass Lake, Minnesota, is a Forest Service form 874-9 by H. M. Kingley dated February 26, 1935. He recovered a 4 feet 6 inches high by 5 inches in diameter Cedar snag west of the road, a distance of 30 feet to the center of the road. He also put a Metal Location Poster on the west side of a 4 inch diameter Aspen that bears NORTH 72 degrees EAST, a distance of 0.55 chains (36.30 feet).

After running an EDM/theodolite traverse through this area the Forest Service survey crew returned here on August 1, 1985. They set a new monument in the centerline of Forest Service road 2752 at the proportionate distances between the Northeast and Southeast Corners of Section 16 using the 1913 Cass county survey distances to proportion from. By comparing the 1913 survey to their survey they found the difference in distance on the north half mile is 1.28 feet and the south half mile is 1.25 feet. I feel this is the best method to reestablish this corner and perpetuate it as shown on the sketch.