

C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the South Quarter Corner of Section 17, Township 141 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass:

On June 5, 1985, found a 2.5 inch (outside diameter) iron pipe with a 3 inch diameter iron cap stamped as shown in the sketch, 3 inches below the road surface. This monument was in good condition so we left it as found.


SKETCH OF REFERENCE TIES
(not to scale)

decl: 5° E

Top of page is NORTH

N 57° W, 57.58 feet to a 16d nail in the northeasterly face of an 11.3 inch diameter White Birch, double blazed and scribed "1/4 S17" and "BT".

FR 2302C



S 45° W, 24.63 feet to a 16d nail in the northwesterly face of a 7.0 inch White Birch, double blazed and scribed "1/4 S20" and "BT".

S 45° E, 15.92 feet to a 16d nail in the northeasterly face of a 9.5 inch diameter Elm, double blazed and scribed "1/4 S20" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date 9-25-85 Registration No. 14677

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 19 85, at 9:35 A.M. and assigned DOCUMENT NUMBER 285570.

Claudine Kayser
County Recorder
m.s.

STATEMENT OF EVIDENCE: South Quarter Corner of Section 17, Township 141 North, Range 25 West, of the 5th Principal Meridian.

This corner was originally established by Edgar P. Putman and William P. Allen, Deputy Surveyors, in April of 1871. The record of that survey is on file in the Office of the Secretary of State, St. Paul, Minnesota. Their notes indicate that a post was set to mark the corner and referenced by: a 10 inch diameter Spruce that bears SOUTH 24 degrees EAST, a distance of 15 links (9.90 feet); a 22 inch diameter Aspen that bears NORTH 5 degrees EAST, a distance of 31 links (20.46 feet).

On May 29, 1920, while traversing around Section 17, John Curo recovered a 12 inch diameter Birch stump. He measured off NORTH 32 degrees EAST, a distance of 21.1 feet and set a new hub. Nowhere in his notes does he state the origin of this witness. This information is contained in the field notes of John Curo, Hackensack, Minnesota.

John Curo returned to this corner on June 4, 1920, and found a 2 foot long by 4 inches square wood post marked "1/4 S". He replaced this post with a 2.5 foot long iron pipe with a 3 inch diameter iron cap stamped as shown on sketch, and two 60d spikes in the bottom of the pipe mounded by stone.

On June 5, 1985, a Forest Service survey crew found a 2.5 inch (outside diameter) iron pipe with a 3 inch diameter iron cap stamped as shown on sketch, 3 inches below the road surface. A search was made for original survey evidence and any other evidence but none was found. This monument does not appear to be disturbed and is the best evidence of this corner position.

The Forest Service survey crew returned to this corner on July 1, 1985, and established new references as shown on the sketch. The record of this survey is on file with the USDA Forest Service, Chippewa National Forest.