

C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the East Quarter Corner of Section 21, Township 141 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.


On July 25, 1985, to mark this corner position, we set a 2.5 inch (outside diameter) by 24 inch long aluminum pipe with a 3 inch diameter domed aluminum cap, 8 inches below the road surface, and stamped as shown.

SKETCH OF REFERENCE TIES
(not to scale)
Top of page is NORTH

decl: 5° E

N 68° E, 40.67 feet to a 16d nail in the northwest face of a 9.4 inch diameter Power Pole.

N 76° W, 50.52 feet to a 16d nail in the southerly face of a 4.0 inch diameter Ash, double blazed, scribed "X" and "BT".



S 50° E, 97.13 feet to a 16d nail in the northerly face of a 6.8 inch diameter Tamarack, double blazed, scribed "1/4 S22" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date 9-25-85 Registration No. 14677

285574
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 1985, at 9:55 A.M. and assigned DOCUMENT NUMBER 285574.

Claudine Kayler
County Recorder
ms

STATEMENT OF EVIDENCE: East Quarter Corner of Section 21, Township 141 North, Range 25 West, of the 5th Principal Meridian.

This corner was originally established by Edgar P. Putman and William P. Allen, Deputy Surveyors, in April of 1871. The record of this survey is on file in the Office of the Secretary of State, St. Paul, Minnesota. Their notes indicate that a post was set to mark the corner and referenced by: a 10 inch diameter Spruce that bears NORTH 35 degrees WEST, a distance of 11 links (7.26 feet); and a 10 inch diameter Cedar that bears NORTH 78 degrees EAST, a distance of 19 links (12.54 feet).

In 1913, J. H. Flynn, Cass County Surveyor, recovered the original government survey evidence as follows: a 10 inch diameter Spruce stump that bears NORTH 35 degrees WEST, a distance of 10 links (6.60 feet); and a 10 inch diameter Cedar that bears NORTH 78 degrees EAST, a distance of 19 links (12.54 feet). He then established: an 11 inch diameter Cedar that bears SOUTH 86 degrees EAST, a distance of 25.0 feet; and a 12 inch diameter Cedar that bears SOUTH 89 degrees WEST, a distance of 25.0 feet. This information can be found in the Cass County SURVEYOR'S RECORDS, Book "C", page 39.

In the Supervisor's Office, Chippewa National Forest, Cass Lake, Minnesota, is a Forest Service form 874-9 by H.M. Kingsley dated February 26, 1935. It states that a 10 inch diameter Cedar snag was found with the scribing "1/4 S 21" visible. No other information was given.

On June 13, 1985, a Forest Service survey crew found a Cedar stump in the northeast quadrant. By measuring the 1913 bearing and distance from this tree puts the corner in the westerly side of an old road.

After running a EDM/theodolite traverse to the point established by the recovered stump from the Northeast Corner of Section 21 it was shown that the difference in distance between the 1913 survey and the Forest Service survey is 0.09 feet. I feel the Cedar stump is the 1913 Cedar bearing tree and I accept this position as a perpetuation of the original government survey and set a new monument and references as shown on the sketch. This information is on file with the USDA Forest Service, Chippewa National Forest.