


**CERTIFICATE OF LOCATION OF GOVERNMENT CORNER**

For the North One-sixteenth Corner on the East Line of Section 8, Township 144 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On May 2, 1985, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch, to mark this corner position.


**SKETCH OF REFERENCE TIES**  
(not to scale)

compass decl: 5° E



N 43° E, 66.14 feet to a 16d nail in the northwesterly face of a 17.0 inch diameter Norway Pine, double blazed and scribed "N1/16 S9" and "BT".

N 6° W, 19.79 feet to a 16d nail in the southwesterly face of an 8.2 inch diameter Jack Pine, double blazed and scribed "N1/16 S8" and "BT".



3.0 ft  
8 foot long metal post with a USFS 54-2 "PROPERTY BOUNDARY" sign attached.

3.0 ft  
8 foot long metal post with a USFS 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.

S 32° E, 31.45 feet to a 16d nail in the southwesterly face of an 11.0 inch diameter Jack Pine, double blazed and scribed "N1/16 S9" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*  
Kenneth L. Whitehorn

Date 9-24-85 Registration No. 14677

285576  
OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nw., 1985, at 10:10 A.M. and assigned DOCUMENT NUMBER 285576.

*Claudia Kayler*  
County Recorder  
*ms*

STATEMENT OF EVIDENCE: The North One-sixteenth Corner on the East Line of Section 8, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original survey of this township by Benjamin C. Baldwin, Deputy Surveyor, in 1876.

No public record was found of establishment or visitations through the intervening years for this corner position. A thorough search was made of the area but no evidence of this corner position was recovered. Based on this information we established this corner position midpoint on the East Line of the Northeast Quarter of said Section 8. The basis for the determination of this point are: Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700, coordinates on the corners of the Public Land Survey System. These coordinates were provided to the USDA-Forest Service (USFS) by Advance Surveying and Engineering Company, Minneapolis, Minnesota, under contract to perpetuate and restore the Public Land Survey System corners in this township.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary.