


C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the Center Quarter Corner of Section 9, Township 144 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On May 9, 1985, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch, to mark this corner position.

SKETCH OF REFERENCE TIES
(not to scale)


compass decl: 5° E



N 43° W, 47.73 feet
to a 16d nail in the
southerly face of a 15.9
inch diameter Norway Pine.

N 34° E, 16.37 feet to a 16d
nail in the northeasterly face
of a 12.9 inch diameter Jack
Pine.

8 foot long metal post with a
USFS 54-2 "PROPERTY BOUNDARY"
sign attached.



3.0 ft
3.0 ft
8 foot long metal post with USFS 54-2
"PROPERTY BOUNDARY" and 54-9 "LAND
SURVEY MONUMENT" signs attached.

S 41° W, 31.41 feet to a 16d nail in the easterly
face of a 16.2 inch diameter Jack Pine.

All bearing trees are double blazed and scribed "C1/4 S9" and "BT", marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date Sep 26, 1985 Registration No. 14677

285578
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov, 19 85, at

10:20 A.M. and assigned DOCUMENT NUMBER 285578.

Claudia Herdich
County Recorder
M.S.

STATEMENT OF EVIDENCE: The Center Quarter Corner of Section 9, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original survey of this township by Benjamin C. Baldwin, Deputy Surveyor, in 1876.

No public record was found of establishment or visitations through the intervening years for this corner position. A thorough search of the area was conducted but no evidence of this corner position was recovered. Based on this information we established this corner position at the intersection of the North-South and East-West Quarter Lines of said Section 9. The basis for the determination of these subdivisional lines are: Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700; coordinates on the corners of the Public Land Survey System. These coordinates were provided to the USDA-Forest Service (USFS) by Advance Surveying and Engineering Company, Minneapolis, Minnesota, under contract to perpetuate and restore the Public Land Survey System corners in this township.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary.