


**CERTIFICATE OF LOCATION OF GOVERNMENT CORNER**

For the Center South One-sixteenth Corner of Section 9, Township 144 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

To mark this corner position, on May 9, 1985, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch.

**SKETCH OF REFERENCE TIES**  
(not to scale)

compass decl: 5° E




N 18° W, 50.00 feet to a 16d nail in the southwesterly face of a 4.0 inch diameter Red Maple scribed "X" and "BT".

8 foot long metal post with USFS 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.

3.0 ft

N 87° E, 33.15 feet to a 16d nail in the southerly face of a 5.9 inch diameter Red Maple scribed "CS1/16 S9" and "BT".



3.0 ft

8 foot long metal post with a USFS 54-2 "PROPERTY BOUNDARY" sign attached.

S 47° W, 36.34 feet to a 16d nail in the northwesterly face of a 12.0 inch diameter Black Spruce scribed "CS1/16 S9" and "BT".

All bearing trees are double blazed and scribed as stated above, marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*  
Kenneth L. Whitehorn

Date Sept 26, 1985 Registration No. 14677

285579  
OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 19 85, at 10:25 A.M. and assigned DOCUMENT NUMBER 285579.

*Claudia Kayler*  
County Recorder  
ms

**STATEMENT OF EVIDENCE:** The Center South One-sixteenth Corner of Section 9, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original survey of this township by Benjamin C. Baldwin, Deputy Surveyor, in 1876.

No record was found of establishment or visitation through the intervening years for this corner position. A thorough search of the area was made but no evidence of this corner location was recovered. Based on this information we established this corner position midpoint and on line between the Center Quarter Corner (as established by us) and the South Quarter Corner of said Section 9. For a complete history on the South Quarter Corner see James Parker, R.L.S., "CERTIFICATE OF LOCATION OF GOVERNMENT CORNER", on file in the Office of the Cass County Recorder as Document Number 281684. The basis for the determination of the subdivisional lines for this section are: Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700; coordinates on the corners of the Public Land Survey System. These coordinates were provided to the USDA-Forest Service (USFS) by Advance Surveying and Engineering Company, Minneapolis, Minnesota, under contract to perpetuate and restore the Public Land Survey System corners in this township.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary.