


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the East One-sixteenth Corner on the South Line of Section 8, Township 144 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On May 17, 1985, to mark this corner position, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES  
(not to scale)

decl: 5° E



N 53° W, 82.01 feet to a 16d nail in the northwesterly face of a 4.9 inch diameter Sugar Maple, double blazed and scribed "E1/16 S8" and "BT".



S 74° W, 78.79 feet to a 16d nail in the northeasterly face of a 7.1 inch diameter White Oak, double blazed and scribed "E1/16 S17" and "BT".



8 foot metal post with USFS 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.

3.0 ft

3.0 ft

8 foot metal post with a USFS 54-2 "PROPERTY BOUNDARY" sign attached.

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*

Kenneth L. Whitehorn

Date Sep 26, 1985 Registration No. 14677

285581  
OFFICE OF THE COUNTY RECORDER  
County of \_\_\_\_\_

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nw, 1985, at 10:35 A.M. and assigned DOCUMENT NUMBER 285581.

*Claudia Kayler*  
County Recorder  
*ms*

**STATEMENT OF EVIDENCE:** The East One-sixteenth Corner on the South Line of Section 8, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original 1876 survey of this township by Benjamin C. Baldwin, Deputy Surveyor, General Land Office.

No record was found of establishment or visitation through the intervening years for this corner position and a thorough search of the area revealed no evidence of this corner position. Based on this information we established this corner position midpoint and on line between the South Quarter Corner and the Southeast Corner of said Section 8. For a complete history of the South Quarter Corner see James Parker, R.L.S., "CERTIFICATE OF LOCATION OF GOVERNMENT CORNER", on file in the Office of the Cass County Recorder as Document Number 281682 and for the Southeast Corner see James Parker, R.L.S., "CERTIFICATE OF LOCATION OF GOVERNMENT CORNER", on file in the Office of the Cass County Recorder as Document Number 281683. The basis for the determination of the subdivisional lines for this section are coordinates provided to the USDA-Forest Service (USFS) by Advance Surveying and Engineering Company, Minneapolis, Minnesota. These coordinates are Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700 and were determined under contract to perpetuate and restore the Public Land Survey System corners in this township.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary.