

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the East One-sixteenth Corner on the South Line of Section 9, Township 144 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.


On May 16, 1985, to mark this corner position, we set a 5/8 inch diameter by 60 inch long aluminum rod with a 3.25 inch diameter aluminum tablet, containing and imbedded magnetized pellet, up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES
(not to scale)

TOP OF PAGE IS NORTH
compass decl: 5° E

N 86° E, 9.44 feet to a 16d nail in the the easterly face of a 6.3 inch diameter Ash, double blazed and scribed "E1/16 S9" and "BT".

8 foot long metal post with a USFS 54-2 "PROPERTY BOUNDARY" sign attached.



8 foot long metal post with USFS 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.

S 50° W, 37.29 feet to a 16d nail in the southeasterly face of a 6.8 inch diameter Ash, double blazed and scribed "E1/16 S16" and "BT".

S 51° E, 75.31 feet to a 16d nail in the southwesterly face of a 12.2 inch diameter Tamarack, double blazed and scribed "E1/16 S16" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date Sept 26, 1985 Registration No. 14677

285582
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 1985, at 10:40 A.M. and assigned DOCUMENT NUMBER 285582.

Claudine Koyler
County Recorder
(M)

STATEMENT OF EVIDENCE: The East One-sixteenth Corner on the South Line of Section 9, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original survey of this township by Benjamin C. Baldwin, Deputy Surveyor, in 1876.

No record was found of establishment or visitation through the intervening years for this corner position. A thorough search of the area was made but no physical evidence of this corner position was found. Based on this information we established this corner position midpoint and on line between the South Quarter Corner and the Southeast Corner of said Section 9. For a complete history of the South Quarter Corner see James Parker, R.L.S., "CERTIFICATE OF LOCATION OF GOVERNMENT CORNER", on file in the Office of the Cass County Recorder as Document Number 281684 and for the Southeast Corner see James Parker, R.L.S., "CERTIFICATE OF LOCATION OF GOVERNMENT CORNER", on file in the Office of the Cass County Recorder as Document Number 281709. The basis for the determination of the subdivisional lines for this section are: Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700; coordinates on the corners of the Public Land Survey System. These coordinates were provided to the USDA-Forest Service (USFS) by Advance Surveying and Engineering Company, Minneapolis, Minnesota, under contract to perpetuate and restore the Public Land Survey System corners in this township.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary.