


C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the Center South One-sixteenth Corner of Section 22, Township 144 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

To mark this corner position, on May 20, 1985, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES
(not to scale)


decl: 5° E



N 61° E, 71.85 feet to a
16d nail in the northwesterly
face of a 19.6 inch diameter Cedar.

8 foot long metal post with a
USFS 54-2 "PROPERTY BOUNDARY"
sign attached.

3.0 ft



3.0 ft

8 foot long metal post with
USFS 54-2 "PROPERTY BOUNDARY"
and 54-9 "LAND SURVEY
MONUMENT" signs attached.

S 58° W, 26.66 feet to a
16d nail in the northwesterly
face of a 6.3 inch diameter
Sugar Maple.

S 30° E, 47.52 feet to 16d
nail in the northeasterly
face of a 5.9 inch diameter
Sugar Maple.

All bearing trees are double blazed and scribed "CS1/16 S22" and "BT", marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date Sep 26, 1985 Registration No. 14677

²⁸⁵⁵⁸⁵
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 19 85, at 10:55 A.M. and assigned DOCUMENT NUMBER 285585.

Claudia Kayler
County Recorder

M.S.

STATEMENT OF EVIDENCE: The Center South One-sixteenth Corner of Section 22, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original survey of this township by Benjamin C. Baldwin, Deputy Surveyor, in 1876.

No record was found of establishment or visitation through the intervening years for this corner position. A thorough search of the area was made but no evidence of this corner location was recovered. Based on this information we established this corner position midpoint and on line between the Center Quarter Corner (mathematically determined) and the South Quarter Corner of said Section 22. For a complete history on the South Quarter Corner see James H. Parker, R.L.S., "CERTIFICATE OF LOCATION OF GOVERNMENT CORNER", on file in the Office of the Cass County Recorder as Document Number 281961. The basis for the determination of subdivisional lines for this section are coordinates provided by Advance Surveying and Engineering Company, Minneapolis, Minnesota, under contract to the USDA-Forest Service (USFS) to perpetuate and restore the Public Land Survey System corners in this township. These coordinates are Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary.