


C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the Center Quarter Corner of Section 28, Township 144 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On May 21, 1985, to mark this corner position, we set a 2.5 inch (outside diameter) by 54 inch long galvanized iron pipe with a break away plastic base containing a magnetized pellet. This iron pipe is capped with a domed brass tablet, 3 inches in diameter, up 24 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES
(not to scale)

decl: 5° E



N 39° E, 72.66 feet to a 16d nail in the southeasterly face of a 7.5 inch diameter Aspen.

N 23° W, 49.61 feet to a 16d nail in the northeasterly face of a 5.8 inch diameter Aspen.

8 foot long metal post with a USFS 54-2 "PROPERTY BOUNDARY" sign attached.

3.0 ft



3.0 ft

8 foot long metal post with USFS 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.

S 69° W, 17.56 feet to a 16d nail in the southerly face of an 11.3 inch diameter Red Maple.

All bearing trees are double blazed and scribed "C1/4 S28" and "BT", marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date 9-24-85 Registration No. 14677

285586

OFFICE OF THE COUNTY RECORDER
County of Cass
I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 19 85, at 11:45 A.M. and assigned DOCUMENT NUMBER 285586.

Claudia Kayler
County Recorder
m.j.

STATEMENT OF EVIDENCE: The Center Quarter Corner of Section 28, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original survey of this township by Benjamin C. Baldwin, Deputy Surveyor, in 1876.

No public record was found of establishment or visitations through the intervening years for this corner position. A thorough search of the area was conducted but no evidence of this corner position was recovered. Based on this information we established this corner position at the intersection of the North-South and East-West Quarter Lines of said Section 28. The basis for the determination of these subdivisional lines are coordinates on the corners of the Public Land Survey System. These coordinates were provided to the USDA-Forest Service (USFS) by Advance Surveying and Engineering Company, Minneapolis, Minnesota, under contract and are Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary.