

**CERTIFICATE OF LOCATION OF GOVERNMENT CORNER**

For the North Quarter Corner of Section 11, Township 141 North, Range 30 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.


On April 20, 1983, to mark this corner position, we set a 2.5 inch (outside diameter) by 24 inch long galvanized iron pipe topped with a 3 inch diameter brass tablet, 2 inches below road surface and stamped as shown in the sketch.

**SKETCH OF REFERENCE TIES**  
(not to scale)

Top of Page is NORTH

decl: 5° E

Center Line MN Trunk Highway 200



3.7 feet

S 10° W, 81.50 feet to a nail on the side of a 4 inch diameter White Oak, double blazed and scribed "1/4S11" and "BT".



S 54° E, 72.10 feet to a nail on the side of an 8 inch diameter White Oak, double blazed and scribed "1/4S11" and "BT".



S 29° E, 86.65 feet to a nail on the side of a 7-inch diameter Red Oak, double blazed and scribed "1/4S11" and "BT".

All bearing trees are marked with red enamel, and a USFS 54-3 "BEARING TREE TAG".

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*

Kenneth L. Whitehorn

Date FEB. 25 1986 Registration No. 14677

287747  
OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 14 day of March, 1986, at 1:50 P.M. and assigned DOCUMENT NUMBER 287747.

*Claudine Kaylor*  
Claudine Kaylor, County Recorder  
M I

**STATEMENT OF EVIDENCE:** North Quarter Corner of Section 11, Township 141 North, Range 30 West of the 5th Principal Meridian.

The plats and field notes, filed in the Office of the Secretary of State, St. Paul, Minnesota, indicate the original township subdivision was done by P. H. Conger, Deputy Surveyor, under contract to the General Land Office (GLO), now the Bureau of Land Management (BLM). These notes, dated September, 1873, state a wood post was set to mark this corner position which was witnessed by: A 20 inch diameter Yellow Pine that bears NORTH 19 degrees EAST, a distance of 64 links (42.24 feet) and a 16 inch diameter Yellow Pine that bears SOUTH 28 degrees EAST, a distance of 121 links (79.86 feet).

In 1917, Earl G. Harrington, U.S. Surveyor of the General Land Office, executed a dependent resurvey and subdivision of sections in this township under instructions in Group 2, Minnesota, issued September 11, 1917. Mr. Harrington recovered a decayed wooden stake with scribe "1/4 S" on the north face of post and the remains of the original bearing trees as follows: A 26 inch diameter pine stump with scribe "BT" which bears NORTH 15 degrees EAST a distance of 64 links (42.24 feet) and a 20 inch diameter pine stump with scribe "BT" which bears SOUTH 28 degrees EAST a distance of 121 links (79.86 feet). To perpetuate this corner position he set a 1 inch diameter by 36 inch long iron post monument with a brass cap marked to identify the corner and witnessed by: A 12 inch diameter White Oak that bears NORTH 3 degrees EAST, a distance of 40 links (26.40 feet) and a 12 inch diameter Red Oak that bears SOUTH 70 degrees WEST, a distance of 153 links (100.98 feet).

The plans and notes for Minnesota Trunk Highway Number 200 are on file in the Brainard office of the Minnesota Department of Transportation. This information which dates from 1938 and 1977 indicates the corner position to be in the road but no ties or description of a monument are given.

Between February 23 and April 18, 1983, a traverse was run by the U. S. Forest Service on the North Line of Section 11. Recovered at this time was the remains of the original southeast bearing tree which was found to be a 20 inch diameter by 20 inch high Norway Pine stump with scribe "1 BT" visible on the hardened face blaze. This stump was tied into the traverse of which the true orientation was based on the U.S.C. & G.S. horizontal control station LEECH 2 and its Azimuth Mark. This corner position was established at record bearing and distance from the recovered pine stump. This re-established position agrees within 00 degrees, 2 minutes, 41 seconds of record GLO Resurvey angle between section corners and within 0.20 feet (+ or -) of the record GLO Resurvey distance between section corners.

On April 20, 1983, M. Hayes, C. Krause, G. Brama, J. Allison, U.S. Forest Service; and T. Freeman, Cass County Surveyor's Office, returned to this position and established the monument and witnesses as shown on the front of this form.