

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the **South Quarter Corner** of Section 19, Township 143 North, Range 26 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On April 16, 1986, to mark this corner position, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe, with a polystyrene base containing an embedded magnetized pellet, and topped with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES

Top of Page is NORTH

(not to scale)


decl: 5° E

N 2° W, 31.97 feet to a 16d nail in the easterly face of an 8.8-inch Red Oak, double blazed and scribed "1/4S19" and "BT"

8 ft. long metal post with USFS 54-2 "PROPERTY BOUNDARY" AND 54-9 "LAND SURVEY MONUMENT" signs attached.

8 ft. long metal post with a USFS 54-2 "PROPERTY BOUNDARY" sign attached.

3.0 ft



S 55° W, 29.13 feet to a 16d nail in the northerly face of a 5.0 inch White Oak, double blazed and scribed "1/4S30" and "BT".

S 07° E, 46.01 feet to a 16d nail in the Westerly face of a 8.1 inch White Oak double blazed and scribed "1/4S30" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date JUN. 17 1986 Registration No. 14677

289676
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 24 day of June, 19 86, at 10:45 A.M. and assigned DOCUMENT NUMBER 289676.

Claudine Kaylor
Claudine Kaylor, County Recorder

ms

STATEMENT OF EVIDENCE: For the South Quarter Corner of Section 19, Township 143 North, Range 26 West of the 5th Principal Meridian.

This corner position was originally established on August 28, 1872, by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office, now the Bureau of Land Management (BLM). The record of this survey is on file in the Office of the Secretary of State, St. Paul, Minnesota, and indicates that a wood post was set to mark the corner position. This post was witnessed by a 5 inch diameter Spruce that bears SOUTH 36 degrees WEST a distance of 26 links (17.16 feet); and a 6 inch diameter Spruce that bears NORTH 35 degrees WEST a distance of 25 links (16.50 feet).

No intervening record of corner visitation was found so I determined the lost position using single proportionate methods. After extensive search of the area failed to reveal any evidence of this corner position we monument the lost position as shown on the front of this document in the single proportionate position.