

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the **South Quarter Corner** of Section 30, Township 143 North, Range 26 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On April 16, 1986, to mark this corner position, we set a 2.5 inch (outside diameter) by 48 inch long galvanized iron pipe, with a polystyrene base containing an embedded magnetized pellet, and topped with a 3 inch diameter brass tablet, flush with ground in road ditch and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES

Top of Page is NORTH


(not to scale)

decl: 5° E

N 50° W, 48.78 feet to a 16d nail in the northeasterly face of a 7.3 inch White Oak, double blazed and scribed "1/4S30" and "BT".

8 ft. steel sign post with 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.

3.0 ft



S 15° W, 126.50 feet to a 16d nail in the westerly face of a 7.1 inch Ash, double blazed and scribed "1/4S31" and "BT".

S 38° E, 126.13 feet to a 16d nail in the easterly face of a 9.6 inch White Oak, double blazed and scribed "1/4S31" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn

 Kenneth L. Whitehorn

Date JUN. 19 1988 Registration No. 14677

289680
OFFICE OF THE COUNTY RECORDER

County of Cass
 I hereby certify that this document was filed in the office of the County Recorder this 24 day of June, 1986, at 10:05 A. M. and assigned DOCUMENT NUMBER 289680.

Claudine Kaylor

 Claudine Kaylor, County Recorder

m.s.

STATEMENT OF EVIDENCE: For the South Quarter Corner of Section 30, Township 143 North, Range 26 West of the 5th Principal Meridian.

This corner was originally set on August 29, 1872, by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office, now the Bureau of Land Management (BLM). The record of this Survey is on file in the Office of the Secretary of State, St. Paul, Minnesota, and indicates that a wood post was set to mark this corner position. This monumented position was referenced by: an 4 inch diameter Oak that bears SOUTH 38 degrees EAST a distance of 10 links (6.60 feet); and an 10 inch diameter Aspen that bears NORTH 19 degrees EAST a distance of 12 links (7.92 feet).

On page 17 of Book 152 in the Office of Walt Curo, R.L.S., Hackensack, Minnesota, is a record of a July, 1920 John Curo visitation to this corner position. This record does not indicate what Mr. Curo found as evidence of this corner position but he states that he established the following witness: a 12 inch diameter Norway Pine that bears SOUTH 32 degrees WEST, a distance of 67 feet 4 inches.

No other intervening record for this corner position was found and we found no physical evidence of this corner position in our search. We did find a fence line to the north that is 2610.42 feet westerly of the Southeast Corner of Section 30. This fits relatively well with Mr. Curo's 1920 distance of 2660 feet. I feel this fence is the best evidence of longitudinal control and the road centerline of County State Aide Highway Number 4 is the best evidence for latitudinal control. We monumented and referenced this obliterated position as shown on the front of this document.