

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the East Quarter Corner of Section 31, Township 143 North, Range 26 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On May 7, 1986, to mark this corner position, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe, with a polystyrene base containing an embedded magnetized pellet, and topped with a 3 inch diameter brass tablet, recessed 0.1 ft. below the ground and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES

Top of Page is NORTH

(not to scale)

decl: 5° E

N 31° E 24.26 feet to an 8 ft. long steel post with a USFS 54-3 "BEARING TREE" tag attached.



S. 81° W, 148.27 feet to a 16d nail in the southerly face of a 19.1 inch Red Oak, double blazed and scribed "1/4 S31" and "BT".

S 57° E, 21.65 feet to an 8 ft. long steel post with a USFS 54-3 "BEARING TREE" tag attached.

S 37° W 149.79 feet, to a 16d nail in the northwesterly face of a 19.8 inch Red Oak, double blazed and scribed "1/4 S31" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date JUN. 19 1986 Registration No. 14677

289682
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 24 day of June, 19 86, at 10:15 A.M. and assigned DOCUMENT NUMBER 289682.

Claudine Kaylor
Claudine Kaylor, County Recorder
Ms

STATEMENT OF EVIDENCE: For the East Quarter Corner of Section 31, Township 143 North, Range 26 West of the 5th Principal Meridian.

This corner position was originally established by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office (GLO), now the Bureau of Land Management (BLM) on August 28, 1872. The record of this survey is on file in the Office of the Secretary of State, St. Paul, Minnesota and indicate a post was set to mark this corner position. This post was witnessed by: a 6 inch diameter White Pine that bears SOUTH 44 degrees EAST, a distance of 15 links (9.90 feet); and a 5 inch diameter White Pine that bears SOUTH 82 degrees WEST, a distance of 5 links (3.30 feet).

Also in the Cass County Recorder's Office on pages 81 thru 85 of SURVEYORS RECORD, Book B, is the 1915 John Curo survey which states he recovered stumps of the original White Pines in the Southeast and Southwest Quadrants. Mr. Curo established the following as new references to this corner position: a 4 inch diameter Poplar that bears NORTH 83 degrees 57 minutes WEST, a distance of 51.4 feet; and a 3 inch diameter Poplar that bears NORTH 40 degrees 19 minutes EAST, a distance of 59.8 feet.

In 1982 the Cass County Surveyor's Office searched for this corner but recovered no evidence.

Our search of this area failed to recover any evidence of this corner position so I used the bearings and distances from the 1915 survey to reestablished Mr. Curo's position which I feel is the best evidence for the location of this corner position and monument the same as shown on the front of this form.