

**CERTIFICATE OF LOCATION OF GOVERNMENT CORNER**

For the **East Quarter Corner** of Section 13, Township 143 North, Range 27 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On June 2, 1986, to mark this corner position, we set a 5/8 inch (outside diameter) by 60 inch long Aluminum Rod and topped with a 3 1/4 inch diameter Aluminum tablet, up 1.2 feet and stamped as shown in the sketch.

**SKETCH OF REFERENCE TIES**  
(not to scale)

Top of Page is NORTH

decl: 5° E

N 20° E, 32.62 feet to a 16d nail in the East side of a 6.0 inch diameter Ash double blazed and scribed "1/4S18" and "BT".

N 80° W, 38.49 feet to a 16d nail in the North side of a 6.7 inch diameter Ash double blazed and scribed "1/4S13" and "BT".

8 ft. Carsonite Boundary post with 54-2a "PROPERTY BOUNDARY" sign attached.  
3.0 ft



3.0 ft  
8 ft. Carsonite Boundary post with 54-2a "PROPERTY BOUNDARY" and LSM 130 "LAND SURVEY MONUMENT" signs attached.

S 13° W, 19.75 feet to a 16d nail in the East side of a 7.9 inch diameter Ash double blazed and scribed "1/4S13" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*  
Kenneth L. Whitehorn

Date JUN. 19 1986 Registration No. 14677

289684  
OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 24 day of June, 1986, at 10:25 A.M. and assigned DOCUMENT NUMBER 289684.

*Claudine Kaylor*  
Claudine Kaylor, County Recorder

**STATEMENT OF EVIDENCE:** For the East Quarter Corner of Section 13, Township 143 North, Range 27 West of the 5th Principal Meridian.

This corner position was originally established by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office (GLO) now the Bureau of Land Management (BLM). On August 23, 1872, Mr. Griffin set a post of unspecified type, to mark this corner position which was witnessed by: a 6 inch diameter Cedar that bears SOUTH 50 degrees EAST, a distance of 7 links (4.62 feet); and a 6 inch diameter Spruce that bears SOUTH 38 degrees WEST, a distance of 6 links (3.96 feet).

No intervening record of any visitation or survey work utilizing this corner position was recovered. A thorough search was conducted but we were unable to recover any physical evidence to indicate this corner position. I determined the lost position for this corner using single proportionate methods and set the monument and references as shown on the front of this document.