

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the **East Quarter Corner** of Section 24, Township 143 North, Range 27 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On April 22, 1986, to mark this corner position, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe, with a polystyrene base containing an embedded magnetized pellet, and topped with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES
(not to scale)

Top of Page is NORTH

decl: 5° E

N 30° E, 41.40 feet to a 16d nail in the southeasterly face of a 7.2 inch Red Oak, double blaze and scribed "1/4S19" and "BT".



3.0 ft.

8 ft. long steel sign post with a USFS 54-9 "LAND SURVEY MONUMENT" sign attached.

S 57° W, 20.89 feet to a 16d nail in the northwesterly face of a 4.8 inch Sugar Maple, double blaze and scribed "1/4S24" and "BT".



S 34° E, 54.86 feet to a 16d nail in the northeasterly face of a 7.8 inch Red Oak, double blazed and scribed "1/4S19" and "BT".



All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn

Kenneth L. Whitehorn

Date JUN. 19 1986 Registration No. 14677

289686
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 24 day of June, 19 86, at 10:35 A.M. and assigned DOCUMENT NUMBER 289686.

Claudine Kaylor
Claudine Kaylor, County Recorder

ms

STATEMENT OF EVIDENCE: For the **East Quarter Corner** of Section 24, Township 143 North, Range 27 West of the 5th Principal Meridian.

This corner position was originally established on August 23, 1872, by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office, now the Bureau of Land Management (BLM). The record of this survey is on file in the Office of the Secretary of State, St. Paul, Minnesota, and indicates that Mr. Griffin set a post to mark this corner position. This record further indicates that Mr. Griffin referenced this corner position with: an 8 inch diameter Birch that bears SOUTH 87 degrees WEST, a distance of 19 links (12.54 feet); and an 8 inch diameter Red Oak that bears NORTH 63 degrees EAST, a distance of 17 links (11.22 feet).

No intervening record of visitation was recovered and after a thorough search of the area I decided that this corner was lost. This lost position was determined by single proportionate methods and monumented and referenced as shown on the front of this document.

