

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the **Southeast Corner** of Section 24, Township 143 North, Range 27 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On March 25, 1986, to mark this corner position, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe, with a polystyrene base containing an embedded magnetized pellet, and topped with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES
(not to scale)

Top of Page is NORTH

decl: 5° E

N 01° E, 40.07 feet to a 16d nail in the easterly face of a 7.8 inch Sugar Maple double blazed and scribed "S19" and "BT".



3.0 ft.

8 ft. long steel sign post with a USFS 54-9 "LAND SURVEY MONUMENT" sign attached.



S 71° W, 5.15 feet to a 16d nail in the northwesterly face of a 5.2 inch diameter Sugar Maple, double blaze and scribed "S25" and "BT".



S 10° E, 38.45 feet to a 16d nail in the easterly face of a 5.2 inch Sugar Maple, double blazed and scribed "S30" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date JUN. 18 1986 Registration No. 14677

289687
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 24 day of June, 1986, at 10:40 A.M. and assigned DOCUMENT NUMBER 289687.

Claudine Kaylor
Claudine Kaylor, County Recorder
ms

STATEMENT OF EVIDENCE: For the **Southeast Corner** of Section 24, Township 143 North, Range 27 West of the 5th Principal Meridian.

This corner position was originally established on August 23, 1872 by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office, now the Bureau of Land Management (BLM). The record of this survey is on file in the Office of the Secretary of State, St. Paul, Minnesota, and indicates that Mr. Griffin set a wood post to mark this corner position. This record further indicates that this corner position was witnessed by: an 8 inch diameter Soft Maple that bears NORTH 64 degrees EAST, a distance of 10 links (6.60 feet); a 9 inch diameter Sugar Maple that bears SOUTH 29 degrees EAST, a distance of 21 links (13.86 feet); a 9 inch diameter Linden that bears SOUTH 62 degrees WEST, a distance of 14 links (9.24 feet); and a 10 inch diameter Sugar Maple that bears NORTH 10 degrees WEST, a distance of 20 links (13.20 feet).

No intervening record was found of any visitation to this corner and our field search failed to reveal any evidence of this corner position. I feel this corner is lost and determined the monumented location, as shown on the front of this document, using single proportionate methods.