

C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the Southeast Corner of Section 25, Township 143 North, Range 27 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On June 3, 1986, to mark this corner position, we set a 2.5 inch (outside diameter) by 24 inch long galvanized iron pipe, with an embedded magnetized pellet, and topped with a 3 inch diameter brass tablet, just below road surface with cap covered, and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES

Top of Page is NORTH


(not to scale)

decl: 5° E

N 08° W, 47.78 feet to a 16d nail in the westerly face of a 5.8 inch Red Oak, double blaze and scribed S25" and "BT".

N 63° E, 107.44 feet to a 16d nail in the southeasterly face of a 12.2 inch White Oak, double blaze and scribed "S30" and "BT".

C.S.A.H. 4



S 03° W, 64.76 feet to a 16d nail in the easterly face of a 5.5 inch White Oak, baseblazed and scribed "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn

Kenneth L. Whitehorn

Date JUN. 18 1986

Registration No. 14677

289689
OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 24 day of

June, 19 86, at

10:50 A.M. and assigned DOCUMENT

NUMBER 289689.

Claudine Kaylor

Claudine Kaylor, County Recorder

ms

STATEMENT OF EVIDENCE: For the Southeast Corner of Section 25, Township 143 North, Range 27 West of the 5th Principal Meridian.

This corner position was originally established on August 23, 1872 by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office, now the Bureau of Land Management (BLM). The record of this survey is on file in the Office of the Secretary of State, St. Paul, Minnesota, and indicates that Mr. Griffin set a wood post to mark this corner position. This record further indicates that Mr. Griffin referenced this corner position with: a 10 inch diameter Fir that bears SOUTH 38 degrees EAST, a distance of 21 links (13.86 feet); an 8 inch diameter Birch that bears SOUTH 78 degrees WEST, a distance of 9 links (5.94 feet); an 8 inch diameter Fir that bears NORTH 40 degrees EAST, a distance of 33 links (21.78 feet); and a 10 inch diameter Birch that bears NORTH 59 degrees WEST, a distance of 13 links (8.58 feet).

On page 17 of Book 152 in the records of Walt Curo, R.L.S., Hackensack, Minnesota is the record of a road survey by John Curo circa 1920. The writing is difficult to decipher but it appears that Mr. Curo found some evidence of this corner but did not add any new witnesses.

Our search of this area failed to reveal any physical evidence of the corner so I chose to use the centerline of County State Aide Highway Number 4 for latitudinal control and an old fence line running northerly for longitudinal control. We monumented and referenced this position as shown on the front of this document.