

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the **North One-sixteenth Corner** on the East Line of Section 36, Township 143 North, Range 27 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On May 22, 1986, to mark this corner position, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe, with a polystyrene base containing an embedded magnetized pellet, and topped with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch.


SKETCH OF REFERENCE TIES

Top of Page is NORTH

(not to scale)

decl: 5° E

N 28° W, 42.78 feet to 16d nail in the side of a 5.9 inch diameter Birch, double blazed and scribed "N1/16 S36" and "BT".



■ fiberglass post with a BM102 "Boundary Marker" decal attached 3.0 feet easterly.

■ fiberglass post with BM102 "Boundary Marker" and LSM130 "Land Survey Monument" decals attached 3.0 feet southerly

S 59° W, 23.59 feet to a 16d nail in the northwesterly face of an 8.5 inch White Oak, double blazed and scribed "N1/16 S36" and "BT".



S 51° E, 76.15 feet to a 16d nail in the southwesterly face of a 9.5 inch twin White Oak, double blazed and scribed "N1/16 S31" and "BT".



All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the base blaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date July 2, 1986 Registration No. 14677

290146
OFFICE OF THE COUNTY RECORDER
County of Cass
I hereby certify that this document was filed in the office of the County Recorder this 16 day of July, 19 86, at 9:10 A.M. and assigned DOCUMENT NUMBER 290146.

Claudine Kaylor
Claudine Kaylor, County Recorder
ms

STATEMENT OF EVIDENCE: For the **North One-sixteenth Corner** on the East Line of Section 36, Township 143 North, Range 27 West of the 5th Principal Meridian.

This corner position was never established during the original August 1872 survey by Eli W. Griffin, Deputy Survey, under contract to the General Land Office (GLO), now the Bureau of Land Management (BLM).

There was no intervening record found of any subsequent visitation to this corner position.

After a thorough search of the area failed to reveal any corner position evidence we established the monument and references, as shown on the front of this document, in the lost position. This lost position was determined using single proportionate methods.