CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the South One-sixteenth Corner on the East Line of Section 10, Township 144 North, Range 30 West of the 5th Principal Meridian, STATE OF MINNESOTA. County of Cass.

On March 24, 1981, to mark this corner position, we set a 2.5 inch (outside diameter) by 30 inch long aluminum pipe with a 3 inch diameter aluminum tablet, up 6 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES

Top of Page is NORTH

(not to scale)

decl: 5° E

N 72° W, 25.08 feet to a nail on the side of a 9 inch diameter Ash, single blazed and scribed "S1/16 S10 BT 2.9 feet~

posts with USFS 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.

S 1/16 S10+S11 3.0 feet

8 foot long steel

N 76° E, 79.93 feet to a nail on the side of an 8 inch diameter Cedar, single blazed and scribed "S1/16 S11 BT".



 5.56° W, 40.13 feet to a nail on the side of a 5 inch diameter Ash, single blazed and scribed "S1/16 S10 BT".

All bearing trees are marked with red enamel, and a USFS 54-3 "BEARING TREE TAG".

Statement of evidence relative to this corner position is on the back. I hereby certify that this survey, plan, or report was prepared by me or under my direct ! supervision and that I am a duly Registered Land Surveyor under the laws of the State of |

Minnesota.

Z/986 Registration No. 14677

2901 OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the office of the County Recorder this _ 16

, 19 86 , at M. and assigned DOCUMENT NUMBER

Claudine Kaylor, County Recorder

STATEMENT OF EVIDENCE: For the South One-sixteenth Corner on the East Line of Section 10, Township 144 North, Range 30 West of the 5th Principal Meridian

This corner position was not monumented in the original Township survey by P. H. Conger, Deputy Surveyor, under contract to the General Land Office in 1875. The notes for this survey are on file in the Office of the Secretary of State, St. Paul, Minnesota.

No intervening history has been recovered that records any monumentation or perpetuation of this corner position.

A search area for this corner position was determined using single proportionate methods based on coordinates determined from an EDMI/Theodolite traverse between the Southeast and East Quarter Corners of said section 10. On March 24, 1981, Gary Brama and Dan Jacobs, USDA-Forest Service (USFS), searched this area for evidence of a corner position but nothing was found. This proportionate position was then monumented and referenced as shown on the front of this document.