


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

WC Meander Corner of Section 36, Township 143, Range 28, 5th P.M.
 STATE OF MINNESOTA, County of Cass


At the corner location shown on the sketch:

- On _____ found a _____
DATE
- left monument as found, lowered monument, removed monument (explain)
- On 9-10-86 placed a 5/8"x10' Aluminum monument for a Witness
DATE
Meander Corner 45' north of Boy River in bag.

Not to scale. SKETCH OF REFERENCE TIES



set 8' carsonite sign posts 3' north and south with LSM 130



no trees available.

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Paul H. G. Coe 9-10-86
SIGNATURE DATE

Registration No. 11395

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

OFFICE OF THE REGISTER OF DEEDS
 County of Cass

I hereby certify that this document was filed in the Reg. of Deeds office at 9:20 A.M. on the 15 day of Sept. A.D., 1986

Register of Deeds Clardine Kayler
 By MS, Deputy

DOCUMENT NO. 291629

STATEMENT OF EVIDENCE

Meander Corner of Section 36, Township 143
north, Range 28 West of the 5th Principal Meridian

1873 GLO set a wood post to mark this corner. There were no
trees available.

1920 GLO resurvey set a stake at 6.78 chs. (447.48') north of
the MC on the south side of the river. No evidence of the
original corner found. No trees available.

1986 Walter E. Curo set a 5/8"x10' Aluminum monument 8' in the
ground for a witness meander corner at 465.52 feet north
of the meander corner on the south side of the river and
1469.70 feet south of the northeast corner of section 36.
This corner is about 45' north of the river