Meander # 25 Corner of Section 2 Township 141 N Range 28 W , 5th PM. STATE OF MINNESOTA, County of CASS At the corner location shown on the sketch: Don 7/14/87 found a 1" US GLO brass cap monument Dieft monument as found, lowered monument, removed monument (explain) On
At the corner location shown on the sketch: \(\text{M} \) On \(\frac{7/14/87}{0ATE} \) found a \(\frac{1"}{US} \) GLO brass cap monument \(\text{CAP monument} \) removed monument (explain) \(\text{On} \) On \(\frac{1}{0ATE} \) placed a \(\frac{1}{0ATE} \) SKETCH OF REFERENCE TIES Not to scale 20" White Pine N 42°W 48.80
On 7/14/87 found a 1" US GLO brass cap monument Dieft monument as found, lowered monument, removed monument (explain) On DATE placed a
Dote Placed a SKETCH OF REFERENCE TIES
SKETCH OF REFERENCE TIES Not to scale 20" White Pine N 42°W 48.80' ** 24" White Pine N 20°W 37.60' 5' 8" Burr Oak N 70°E 12.90' SWAMP 6' Steel sign post
SKETCH OF REFERENCE TIES Not to scale 20" White Pine N 42°W 48.80' ** 24" White Pine N 20°W 37.60' 5' \$8" Burr Oak N 70°E 12.90' SWAMP 6' Steel sign post
Not to scale 20" White Pine N 42°W 48.80' 24" White Pine N 20°W 37.60' 8" Burr Oak N 70°E 12.90' SWAMP 6' Steel sign post
20" White Pine N 42°W 48.80' * 24" White Pine N 20°W 37.60' 5'
SWAMP N 20°W 37.60' 8" Burr Oak N 70°E 12.90' 6' Steel sign post
SWAMP N 20°W 37.60' 8" Burr Oak N 70°E 12.90' 6' Steel sign post
SWAMP N 20°W 37.60' 8" Burr Oak N 70°E 12.90' 6' Steel sign post
SWAMP 6' Steel sign post
SWAMP 6' Steel sign post
6' Steel sign post
6' Steel sign post EAST 4.15'
Trees double blazed, scribed, painted red and 54-3 Bearing Tree tag attached. Measurement taken to nail in side of tree.
Statement of evidence relative to this corner location is on back of page.
I hereby certify that this document and the data contained herein was prepared by me or under County of
my direct supervision. I hereby certify that this document was filed in
the Co. Recorders office at $\frac{9:00}{4}$ A. M. on the $\frac{16}{16}$ day of $\frac{9:00}{16}$ A.D., 19 87
Registration No. 11395 County Recorder Clouder Kaylor
□ County Surveyor By No. 301665

Statement of Evidence: Meander Corner #25, Section 2, T.141 N., R.28 W., 5th P.M.

- 1873 US General Land Office survey set a wood post for this corner and marked the following bearing tree: 12" Poplar S 25°E 20 1ks.
- 1921 US General Land Office dependent resurvey found no evidence of the original corner and set a 1"x36" I.P. with marked brass cap. The following bearing trees were marked
- 10" W.Oak N 3°E 109 lks.,8" N.Pine S 51½°E 206 lks. 1972
- US Forest Service personnel found remains of the GLO survey and documented in Forest Service records. 1921 W.Oak is now a 20" W.Oak at bearing & distance-rescribed, N.Pine is now a 18" N. Pine at bearing & distance-scribe visible. No new monument set, as GLO monument is in good condition. The following bearings were marked: 18" N.Pine N 35°W 49.50' scribed "MC S35 BT", steel sign post 6'long EAST 4.20' with signs 54-2 & 54-4. William Okerman filed CERTIFICATE OF LOCATION OF GOVERNMENT CORNER.
- 1987 Walt curo, under contract with the Forest Service, finds GLO monument and 1972 BT and sign post. He marks new bearings as shown on front of this certificate and files this certificate to update the 1972 certificate.