

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

S-SE 1/64 Corner of Section 1, Township 141 N., Range 28 W., 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:


On 7/15/87 found a US GLO brass cap monument
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES

Not to scale



 4" Burr Oak
 N 30°W 26.00'
 (1973 BT)

8" Burr Oak
 S 78°W 20.1' 
 (1973 BT)

 10" Burr Oak
 S 7°E 4.90'
 (1973 BT)

Trees double blazed, scribed, painted red and 54-3 Bearing Tree tag attached. Measurement taken to nail in side of tree.

Statement of evidence relative to this corner location is on back of page. 301678

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Walter P. Coon 11-23-87
SIGNATURE DATE

Registration No. 11395

- Land Surveyor
- County Surveyor

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 10:10 A .M. on the 16 day of Dec. A.D., 19 87

County Recorder *Clairine Kugel*

By *ms*, Deputy

DOCUMENT NO. 301678

Statement of Evidence: S-SE 1/64 Corner, Section 1, T.141 N., R.28 W., 5th P.M.

- 1919 US General Land Office dependent resurvey set a 1"x36" I.P. with marked brass cap. No bearing trees were marked.
- 1973 US Forest Service personnel found the brass cap monument in good condition. Marked 3 bearing trees: 3"W.Oak N 35°W 26.0' scribed "X BT", 4"W.Oak S 74°W 20.1' scribed "AP3 BT", 7" W.Oak S 7°E 4.9' scribed "AP3 BT", 6' steel sign post EAST 4.5'. William Okerman filed a CERTIFICATE OF LOCATION OF GOVERNMENT CORNER.
- 1987 Walt Curo, under Forest Service contract, found US GLO brass cap monument in good condition and all 3 1973 BT's. He files this certificate to update the 1973 certificate.