

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

S-S 1/64 Corner of Section 1, Township 141 N., Range 28 W., 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:


On 7/15/87 found a 6"x6"x24" concrete monument with brass tablet, down 10"
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES

Not to scale



12" Burr Oak
N 78°W 54.60'
(1978 BT)

14" Red Oak
N 31°E 68.55'
(1978 BT)

15" Burr Oak
N 61°E 68.00'
(1978 BT)

Trees double blazed, scribed, painted red and 54-3 Bearing Tree tag attached.
Measurement taken to nail in side of tree.

Statement of evidence relative to this corner location is on back of page. 301679

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Walter E. Conn 11-23-87
SIGNATURE DATE

Registration No. 11395

- Land Surveyor
 County Surveyor

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 10:15 A.M. on the 16 day of Dec. A.D., 19 87

County Recorder Clairine Kaye

By MS, Deputy

DOCUMENT NO. 301679

Statement of Evidence: S-S 1/64 Corner, East Line Section 1, T.141 N., R.28 W., 5th P.M.

- 1918 US General Land Office dependent resurvey set a 1"x36" I.P. with marked brass cap, 36" in ground. No bearing trees were marked.
- 1972 US Forest Service personnel did not find GLO monument, probably graded out.
- 1978 US Forest Service personnel set a 6"x6"x24" concrete monument with brass tablet proportionally. Marked bearings: 12" Red Oak N 37°E 68.70', 12" W. Oak N 66°E 68.09', 8" Twin W. Oak N 73°W 54 65', all scribed "SS1/64 BT", steel sign post WEST 22.1'
- 1987 Walt Curo, under Forest Service contract, found concrete monument with brass cap and all 3 1978 BT's.