

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner of Section 27, Township 141 N., Range 31 W., 5th P.M.


STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

- On 10/20/87 found a 2 3/4" x 60" capped I.P.
DATE
- left monument as found, lowered monument, removed monument (explain)
- On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES

Not to scale



10" Red Oak
N 75°W 21.3'

12" Red Oak
N 46°E 18.71'
(old BT)

8" Red Oak
S 39°W 14.50'
(old BT)

Trees double blazed, scribed, painted red and 54-3 Bearing Tree tag attached.
Measurement taken to nail in side of tree.

Statement of evidence relative to this corner location is on back of page.

302143

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Walter C. Row
SIGNATURE

12-26-87
DATE

Registration No. 11395

- Land Surveyor
 County Surveyor

OFFICE OF THE COUNTY RECORDER

County of Con

I hereby certify that this document was filed in the Co. Recorders office at 3:20 P .M. on the 6 day of January A.D., 19 88

County Recorder Claudia Kayler

By ms, Deputy

DOCUMENT NO. 302143

Statement of Evidence: Northeast Corner Section 27, T.141 N., R.31 W., 5th P.M.

- 1873 US General Land Office survey set a wood post for this corner and marked the following bearing trees: 10" Poplar N 77 E 10 lks., 10" Poplar N 55 W 28 lks., 6" Oak S 40 W 38 lks., 18" Y.Pine S 55 E 12 lks.
- 1920 County Survey Record Book "C", page 460, shows a survey by E.B. Horst. He found the NE & NW BT's and stump of the SE BT. He set a 2"x48" I.M. The following BT's were marked: 10" W.Oak S 54 E 60', 12" W.Oak N 86-30 W 24.5'
- 1922 County Resurvey Plat filed in the Cass County Recorders Office in cabinet "E", number 53, by E.B.Horst shows a 2"x48" I.M.
- 1952 County Survey Record Book "D", page 400, shows a survey by Harold Curo. He found the 2½"x48" I.M. with cap. The following bearing trees were marked: 16" W.Pine N 46-42 E 56.10', 6"W.Pine N 38 W 53.50', 8"Poplar S 15-35 W 23.25', 8"Poplar S 54-40 E 13.80'
- 1959 Harold Curo, RLS #3417, files Certificate of Location of Government Corner. He replaced the 2" I.P. with a 2 3/4" x60" capped I.P. filled with concrete. The following bearings were marked: 9" Red Oak N 42-14 E 18.75', 8" Red Oak N 45-38 W 17.80', 6" Red Oak S 37-56 W 14.60'
- 1962 US Forest Service technician R.H.McDonald, notes corner found at W. end of rock fence row, approx. 2' high & 100' long.
- 1987 On Oct. 20, I found the 2 3/4"x60" I.P. and BT's as per 1959 H.Curo certificate. I file this certificate to update the 1959 certificate.