

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 34, Township 141 N., Range 31 W., 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

On 10/20/87 found a 2 3/4" x 60" capped iron monument

DATE


left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____

DATE

SKETCH OF REFERENCE TIES

Not to scale



14" Burr Oak
N 14 W 45.25'
(1980 BT)

8" Burr Oak
N 53 W 36.54'
(1959 BT)

10" Burr Oak
S 34 W 34.85'
(1959 BT)

Trees double blazed, scribed, painted red and 54-3 Bearing Tree tag. Measurement taken to nail in side of tree.

Statement of evidence relative to this corner location is on back of page.

302147

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Walter E. Dean
SIGNATURE

12-26-87
DATE

Registration No. 11395

Land Surveyor

County Surveyor

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 3:45 P.M. on the 6 day of January A.D., 19 88

County Recorder Claudine Kayler

By ms, Deputy

DOCUMENT NO. 302147

Statement of Evidence: North Quarter Corner Section 34, T.141 N., R.31 W.,
5th P.M.

- 1873 US General Land Office survey set a wood post for this corner and marked the following bearing trees: 5" Maple S 17 W 18 lks., 4" Ironwood N 23 E 19 lks.
- 1928 County Resurvey Plat by John Greene shows an iron monument. Filed in the Cass County Recorders Office in cabinet "E", number 55.
- 1959 Harold Curo found the 2"x48" boiler flue for the corner. He set a 2 3/4"x60" capped iron monument. He marked new BT's: 5" White Oak N 52-57 W 36.65', 10" Jack Pine N 15-11 E 43.20', 5" White Oak S 33 W 35.1'. He filed a Certificate of Location of Government Corner.
- 1987 Walt Curo, under Forest Service contract, finds the capped iron monument and 1959 BT's. I file this certificate to update the 1959 certificate.