

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner of Section 16, Township 141, Range 27, 5th P.M.

STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

On 10-20-1987 found a brass capped concrete monument
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

Monument Marked:

SKETCH OF REFERENCE TIES
NOT TO SCALE

T141N R27W

S9 | S10

S16 | S15

1968

RLS 6807

Sec. 9

Sec. 10

A 20d spike in a 12"
Red Pine, N 28° W,
83.56 feet (1968 BT)

A 20d spike in a 12"
White Oak; N 41° E,
60.76 feet (1968 BT)

Centerline of County Road 129

5±

A 20d spike in a 13"
Jack Pine, S 74° W,
64.95 feet (1968 BT)

A 4" x 4" Cedar Post with USFS
54-2 and 54-4 signs, South,
15.6 feet

A White Oak stub,
S 37° E, 62.98 feet
(1968 BT)

Sec. 16

Sec. 15

An 8' steel sign post and sign,
South, 18.9 feet

Bearings: Magnetic

All trees tagged with USFS 54-3 tag.

Statement of evidence relative to this corner location is on back of page.

302620

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Robert L. [Signature]

Date 2-2-88 Registration No. 16459

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 3:40 P.M. on the 5 day of February, A.D., 1988

County Recorder Claudine Kayler

By MS, Deputy

DOCUMENT NO. 302620

Statement of Evidence:

Northeast corner of Section 16

1-9-1874 P.H. Conger, Deputy Surveyor, set a post for corner and witnessed as follows:

Oak 8" North 42 degrees West 15 links (9.90 feet)
Poplar 5" South 43 degrees West 11 links (7.26 feet)
Poplar 5" South 49 degrees East 16 links (10.56 feet)

Said records are filed with the Secretary of State, St. Paul, MN.

1919 Donald Clement, U.S. Surveyor, in a GLO resurvey found a 2 inch galvanized iron pipe purported to have been set by the County Surveyor, in the center of an East-West road, no evidence of original bearing trees and set a 2" x 3' iron post with a brass cap and witnessed as follows:

Norway Pine 24" North 22 degrees East 141 links (93.06 feet)

Said records are filed with the Secretary of State, St. Paul, MN.

6-19-1968 W. Okerman, USFS, found a 2" x 3' iron post, brass cap knocked off, found burned out stump at North 22 degrees East 93 feet. Said records are on file with the USFS in Cass Lake, MN.

6-24-1968 L. Elliot, USFS, set a 6"x 24" cylindrical concrete monument with 3 inch brass tablet down 1 foot in road, and witnessed as follows:

Red Pine 9" North 28 degrees West 83.56 feet

White Oak 10" North 41 degrees East 60.76 feet

White Oak 8" South 37 degrees East 62.98 feet

Jack Pine 10" South 74 degrees West 64.95 feet

4' Cedar post with 54-2 and 54-4 signs, South, 15.6 feet Said records are on file with the USFS in Cass Lake, MN.

11-5-1968 W. Okerman, USFS, visited corner and filed an Affidavit as to Location of Government Corner in the office of the Cass County Register of Deeds on 2-19-1971.

10-20-1987 Personnel of Kovanen Surveying found a 6" concrete monument with 3" brass cap, 0.5' down in road and found witnesses as follows:

Red Pine 12" North 28 degrees West 83.56 feet

White Oak 12" North 41 degrees East 60.76 feet

White Oak 8" South 37 degrees East 62.98 feet (stub)

Jack Pine 13" South 74 degrees West 64.95 feet

4"x 4" Cedar post with 54-2 and 54-4 signs, South, 15.6 feet

This position is a perpetuation of the 1919 GLO Resurvey.