

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

EAST QUARTER Corner of Section 20, Township 141 N, Range 29 W, 5th P.M.  
STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch: Latitude: 47° 00' 54.024"  
Longitude: 94° 21' 53.488"

On \_\_\_\_\_ found a \_\_\_\_\_  
DATE


left monument as found,  lowered monument,  removed monument (explain)

On 7/26/88 placed a 2" x 48" iron monument with a brass cap  
DATE

Magnetic Decl: 5° East  
Not to Scale

### SKETCH OF REFERENCE TIES

All distances are horizontal to nail in side of tree.



9" Norway Pine  
S 74 W 33.36'



8" Norway Pine  
S 13 W 23.11'



7" Norway Pine  
S 42 E 29.50'

Monument is located 110' more or less westerly of United States Forest Service Road #2108 in a Norway Pine Plantation, line to standard west  
8' steel sign post West 5.0'  
8' steel sign post East 5.0'

Monument Stamped

T 141 N R 29 W

S 20 | S 21

All trees are painted with red enamel and marked with a 54-3 (Bearing Tree) tag.

1988

RLS No. 17008

Statement of evidence relative to this corner location is on back of page. 310042

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

David S. Landecker  
David S. Landecker  
Date 1-18-89 Registration No. 17008

OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 10:10 A.M. on the 25 day of January A.D., 1989

County Recorder Claudine Kayler  
By ms, Deputy

DOCUMENT NO. 310042

Statement of Evidence:

East Quarter Corner Section 20, Township 141  
North, Range 29 West, Cass County, Minnesota

P-9 141-29  
Bk.6 Pg.6

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 29 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: an 8 inch Poplar South 83 degrees East a distance of 9 links; and a 3 inch Oak South 75 degrees West a distance of 12 links.

1937 U.S. Forest Service records show the following: J. A. Ghelhaug, for tower survey, established corner at lost single proportion position between the Northeast and Southeast Corner of said Section 20.

1986 U.S. Forest Service crews set an aerial target in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on July 1 a Landecker-Stevenson & Associates crew searched for the corner using computations to determine search area. The following information was found: no evidence of original position; found a 1/2 inch iron rod 3.3 feet northerly of computed position, no idea of origin. Not typical monument as set by Ghelhaug in other corner position. 1/2 inch rod not accepted.

1988 on July 26 a Landecker-Stevenson & Associates crew set a 2 inch by 48 inch iron pipe with brass cap at lost single proportion position between the Northeast and Southeast Corners of said Section 20 as established in 1937 Ghelhaug survey. 3 bearing trees are shown on front of this certificate, two 8 foot steel sign posts are in place as noted.