CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
Meander Corner of Sections 2	7/34,Township 141 N, Range 30 W, 5th P.M.
STATE OF MINNESOTA, County ofCass	
At the corner location shown on the sketch:	Latitude: 46° 59' 38.386" Longitude: 94° 27' 54.908"
□ On found a	
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
On 1/25/89 ploced a 2 inch by 48 inch iron pipe with brass cap, plastic base and magnet.	
Magnetic Decl: 5° East SKETCH OF R Not to Scale	EFERENCE TIES All distances are horizontal to nail in side of tree N 5 W 63.53'
5" Burr Oak N 40 W 29.20	Bluebill Lake
Monument is located 20 feet, more or less, Westerly of marsh edge of Bluebill Lake. 8' steel sign post North 2.65'	
l	Monument Stamped T 141 N R 30 W  Burr Oak 527 MC 734 MC
1989 All trees are painted with red enamel and RLS 17008 marked with a 54-3 (bearing tree) tag.	
Statement of evidence relative to this corner location is on back of page. $310878$	
I hereby certify that this survey, plan or report was prepared by me or under my	OFFICE OF THE COUNTY RECORDER County of
direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Mignesota.  David S. Landecker Date 3/0/89 Registration No. 17008	I hereby certify that this document was filed in the Co. Recorders office at 3:30 P. M. on the 14 day of March A.D., 19 £9  County Recorder Clandine Kaylor  By MS, Deputy  DOCUMENT NO. 310 £78
	DOCUMENT INC.

## Statement of Evidence:

Meander Corner Number 8, Section 34, Township 141 North, Range 30 West, Cass County, Minnesota

V14-15 141-30 Bk.5 Pg.63

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 30 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 12 inch White Pine North 54 degrees West a distance of 37 links; and a 12 inch White Pine South 44 degrees West a distance of 119 links.

1986 U.S. Forest Service crews set an aerial target in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on September 22 a Landecker-Stevenson & Associates crew searched for the corner. No evidence of Pine stumps or corner post from the original survey was found.

1989 on January 25 a Landecker-Stevenson & Associates crew set a 2 inch by 48 inch iron pipe with brass cap, plastic base and magnet at the lost single proportion position between the Northwest and Northeast Corners of Section 34. New bearing trees were marked as shown and steel sign post was set as noted on front of this certificate.