

Statement of Evidence:

East Quarter Corner Section 19, Township 141
North, Range 30 West, Cass County, Minnesota

P-5 141-30
Bk.5 Pg.32

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 30 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: an 8 inch Poplar North 84 degrees East a distance of 24 links; and a 10 inch Oak South 32 and 1/2 degrees West a distance of 19 links.

1964 U.S. Forest Service records show the following: Ekstrom chained from the Southeast Corner of this Section to this location and found no evidence.

1986 U.S. Forest Service crews set an aerial target, in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on August 1 a Landecker-Stevenson & Associates crew searched for the corner. The following information was found and noted: search area near corner, it is mostly mature Aspen with some hardwoods present, several large White Pines and several burnt pine stumps. No evidence of original corner or its accessories.

1988 on October 5 a Landecker-Stevenson & Associates crew set a 2 inch by 54 inch iron pipe with brass cap, plastic base and magnet at the lost single proportion position between the Northeast and Southeast corners of Section 19. New bearing trees were marked as shown on the front of this certificate and steel sign post is in place as noted.