

Statement of Evidence:

East Quarter Corner Section 20, Township 141
North, Range 30 West, Cass County, Minnesota

P-9 141-30
Bk.5 Pg.37

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 30 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 14 inch Yellow Pine South 88 and 1/2 degrees West a distance of 21 links; and a 12 inch Yellow Pine South 55 degrees East a distance of 21 links.

1926 County Surveyor's Record Book 133 pages 103-115 show survey by John Greene; a 9 inch Jack Pine South 68 degrees West a distance of 93.6 feet; and a 9 inch Jack Pine South 83 degrees East 22.27 feet.

1965 U.S. Forest Service records show the following: Technician Ekstrom searched for corner, no evidence found, corner falls in burnt over area.

1986 U.S. Forest Service crews set an aerial target in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on September 21 a Landecker-Stevenson & Associates crew searched for the corner. The following information was found and noted: corner falls in Pine plantation, no evidence left of original bearing trees or 1926 Greene survey remain to be found.

1988 on October 7 a Landecker-Stevenson & Associates crew set a 2 inch by 48 inch iron pipe with brass cap, plastic base and magnet at the lost single proportion position between the Northeast and Southeast corners of Section 20. No trees near available for marking witness ties, set 8 foot steel posts for ties in place as shown. Monument is located in swamp area.