

Statement of Evidence:

Northeast Corner Section 29, Township 141 North,
Range 30 West, Cass County, Minnesota

R-9 141-30
Bk. 5 Pg. 43

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 30 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 13 inch Red Oak North 46 and 1/2 degrees West a distance of 56 links; a 11 inch Red Oak North 20 degrees East a distance of 61 links; a 9 inch White Pine South 71 and 1/2 degrees East a distance of 34 links; and an 8 inch Maple South 78 and 1/2 degrees West a distance of 49 links.

1965 U.S. Forest Service records show the following: Ekstrom chained from West to area of this corner and found no evidence.

1986 U.S. Forest Service crews set an aerial target in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on August 11 a Landecker-Stevenson & Associates crew searched for the corner. No corner or original evidence was found at this position.

1988 on December 13 a Landecker-Stevenson & Associates crew set a 2 inch by 48 inch iron monument with brass cap and plastic base with magnet. Said corner being set at the lost double proportionate position between the Northeast corner at Section 20, the Northeast corner of Section 30, the North Quarter corner of Section 28 and the Northeast corner of Section 32 said township. New bearing trees were marked as shown and steel sign post set as noted on front of this certificate. This position also fit the geographical ties as noted in the original survey, and perpetuated this corner position, being 320 feet, more or less, westerly of a swamp.