

Statement of Evidence:

Meander Corner Number 13, Section 22, Township
141 North, Range 30 West, Cass County,
Minnesota

R15-16 141-30
Bk.5 Pg.47

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 30 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 8 inch Birch South 70 degrees West a distance of 84 links; and a 6 inch Birch North 60 degrees West a distance of 70 links. He did not measure across the lake, just measured to this position and stopped.

1964 U.S. Forest Service technician Ekstrom searched for the corner and found nothing.

1986 U.S. Forest Service crews set an aerial target in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on September 9 a Landecker-Stevenson & Associates crew searched for the corner using computations to determine search area. The following information was found and noted: no evidence of original corner or accessoried found.

1989 on January 27 a Landecker-Stevenson & Associates crew set a 2 inch by 48 inch iron pipe with brass cap, plastic base and magnet, at the computed lost corner position, determined from the Southwest corner of said Section 22 on a line established on a mean bearing between the north line of Section 22 and the south line of Section 27. The same distance was used as measured in the original land office survey of 1873. All measurements were taken from the Southwest corner of said Section 22. New bearing trees were marked as shown on front of this certificate and steel sign post is in place as noted.