

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter _____ Corner of Section 32, Township 141 N, Range 30 W, 5th P.M.

STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

Latitude: 46° 59' 13.468"
Longitude: 94° 29' 29.873"


On _____ found a _____
DATE

left monument as found, lowered monument, removed monument (explain)

On 10/5/88 placed a 2 inch by 54 inch iron pipe with brass cap
DATE

Magnetic Decl: 5° East SKETCH OF REFERENCE TIES
Not to Scale

All distances are horizontal to nail in side of tree.



8" Burr Oak
N 10 W 35.29'

10" Burr Oak
N 20 E 42.59'

7" Burr Oak
S 72 E 28.76'

Monument is located on a southerly running ridge with medium sized low area 75 feet, more or less, east. Very small low area 50 feet, more or less, west and large low area 300 feet, more or less, westerly.
8' Sign post South 5.0'
8' Sign post East 5.0'

Monument Stamped
T 141 N R 30 W

S32+S33
1988

RLS 17008

All trees are painted with red enamel and marked with a 54-3 (bearing tree) tag.

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

David S. Landecker
David S. Landecker

Date 3/31/89 Registration No. 17008

311182

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 1:00 P.M. on the 3rd day of April A.D., 19 89

County Recorder Claudio Kaylow
By bjk, Deputy

DOCUMENT NO. 311182

Statement of Evidence:

East Quarter Corner Section 32, Township 141
North, Range 30 West, Cass County, Minnesota

X-9 141-30
Bk.5 Pg.74

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 30 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 10 inch Red Oak North 77 and 1/2 degrees East a distance of 19 links; and a 12 inch Poplar North 73 degrees West a distance of 75 links.

1937 Civilian Conservation Corps records show a measurement along the West line of Section 33. No Quarter corner was indicated or shown for this position.

1986 U.S. Forest Service crews set an aerial target in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number: 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on October 5 a Landecker-Stevenson & Associates crew searched for the corner. The following information was found and noted: searched area around target, no evidence found of original bearing trees or post.

1988 on October 5 a Landecker-Stevenson & Associates crew set a 2 inch by 54 inch iron pipe with brass cap and base with magnet at the lost, single proportion position between the Northeast and Southeast corners of Section 32. New bearing trees were marked as shown and a steel sign post set as noted on front of this certificate.