

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Number 11 Meander Corner of Sections 30/31, Township 141 N, Range 29 W, 5th P.M.

STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

Latitude: 46° 59' 37.752"
 Longitude: 94° 23' 48.864"


On _____ found a _____
DATE

left monument as found, lowered monument, removed monument (explain)

On 1/17/89 placed a 2" by 48" iron pipe with brass cap, plastic
DATE
base and magnet.

Magnetic Decl: 5° East SKETCH OF REFERENCE TIES
 Not to Scale

All distances are horizontal to nail in side of tree.



Monument is located
 87'± Easterly of waters edge
 or 75'± Easterly of high water
 mark of Stocking Lake.
 8' steel sign post West 5.0'

Monument Stamped
 T 141 N R 29 W
 MC S30
S31
 1989
 RLS 17008

All trees are painted with red enamel and marked with a 54-3 (bearing tree) tag.

Statement of evidence relative to this corner location is on back of page. 311854

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

David S. Landecker
 David S. Landecker
 Date 4-28-89 Registration No. 17008

OFFICE OF THE COUNTY RECORDER
 County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 4:02 P.M. on the 3 day of May A.D., 1989
 County Recorder Claudia Kayler
 By MS, Deputy
 DOCUMENT NO. 311854

Statement of Evidence:

Meander Corner Number 11 Sections 30 and 31,
Township 141 North, Range 29 West, Cass County,
Minnesota

V2-3 141-29
Bk.4 Pg.65

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 29 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 24 inch White Pine North 16 degrees East a distance of 50 links; and a 5 inch Oak South 62 degrees East a distance of 7 links.

1986 U.S. Forest Service crews set an aerial target in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on July 7 a Landecker-Stevenson & Associates crew searched for the corner. The following information was found and noted: 1 large Oak but does not fit for ties or have scribing; 2 burned Pine stumps but they are not big enough. This corner was determined lost.

1989 on January 17 a Landecker-Stevenson & Associates crew set a 2 inch by 48 inch iron pipe with brass cap, plastic base and magnet at the lost, single proportionate position between the Northwest and Northeast corners of Section 31. New bearing trees were marked as shown and a steel sign post set as noted on front of this certificate.