

Statement of Evidence:

East Quarter Corner Section 29, Township 141
North, Range 29 West, Cass County, Minnesota

T-9 141-29
Bk.4 Pg.62

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 29 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 4 inch Maple North 33 degrees East a distance of 11 links; and a 10 inch Oak South 44 degrees West a distance of 11 links.

1937 J.A. Gjelhaug searched for this corner while surveying in Section 20. He did not find any evidence of the corner.

1965 Ekstrom searched for this corner, but found no evidence of original monument. His notes show the following bearing trees marked: a 7 inch Birch North 74 degrees East; and an 8 inch Tamarack Northwest.

1986 U.S. Forest Service crews set an aerial target in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on July 7 a Landecker-Stevenson & Associates crew searched for the corner. The following information was found and noted: position falls North 9 feet from Forest Service Location Poster (which states North 3 feet to approximate corner). No evidence of original bearing trees or post.

1988 on December 7 a Landecker-Stevenson & Associates crew set a 2 inch by 48 inch iron pipe with brass cap and plastic base at the lost, single proportion position between the Northeast and Southeast corners of Section 29. New bearing trees were marked as shown and steel sign posts set as noted on front of this certificate.