

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER


East Quarter Corner of Section 12, Township 143N, Range 26W, 5th P.M.
 STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:


- On 7-14-1989 found a 24" rod with copper cap.
DATE
- left monument as found, lowered monument, removed monument (explain)
- On _____ placed a _____
DATE

Monument Marked

SKETCH OF REFERENCE TIES
 not to scale



Aluminum Post ■
 N52°W 31.90
 (1976)
 SEC. 12



■ Aluminum Post
 N31°E 42.20
 (1976)

SEC. 7
 ✕ 18" White Pine
 S65°E 44.68

bearings are true All trees are scribed, painted with a 30d spike in side with USFS 54-3 tag.

Statement of evidence relative to this corner location is on back of page. 319611

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

William C. [Signature]

Date 3/20/90 Registration No. 17767

OFFICE OF THE COUNTY RECORDER
 County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 9:45 A .M. on the 12 day of April A.D., 19 90

County Recorder Claudia Kayla
 By MJ, Deputy

DOCUMENT NO. 319611

Statement of Evidence:

G25 East quarter corner section 12

1/4 Cor. 12 and 7 (E 1/4 Cor. Sec. 12)

- 1872 U.S. General Land Office survey set wood post for corner and the following references were noted:
White Pine 8" S 65 degrees W, 9 Links (5.94 feet)
Spruce 6" N 36 degrees E, 12 Links (14.52 feet)
- 1916 E.B. Horst, Cass County Book C, Page 172, found the following witness:
White Pine 8" S 65 degrees W, 9 Links
he added the following witnesses:
White Pine 16" S 63 degrees 15 minutes E, 49.5 feet
White Birch 16" N 18 degrees W, 36.5 feet
- 2-12-1962 USFS corner card states J. Roles and R. Tucker, found fence corner on west side of road, no post or BT's, they placed a tag on corner post.
- 11-8-1965 James Ekstrom, USFS, found 1962 tag, a burned out pine stump that could be Flynns BT.
- 1976 BLM dependent resurvey, found no original evidence, at proportionate distance they set a copperweld, with copper cap, 6" below surface of FS road #126 and witnessed as follows:
Aluminum Post 2.5"x 28" N 31 degrees E, 42.2 feet
Aluminum Post 2.5"x 28" N 52 degrees W, 31.9 feet
Power Pole NW has USFS tag.
- 1979 Olsen, USFS, found 1976 BLM monument.
- 7-25-1989 Personnel from Kovanen & Osufsen Inc. found 1976 BLM monument in good condition and the following witnesses:
Aluminum Post 2.5"x 28" N 31 degrees E, 42.20 feet
Aluminum Post 2.5"x 28" N 52 degrees W, 31.90 feet
we add the following witness:
White Pine 18" S 65 degrees E, 44.68 feet

This position is not traceable to the original GLO corner, but accepted as corner for lack of further evidence.