

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 12, Township 143N, Range 26W, 5th P.M.




STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:



- On _____ found a _____
DATE
- left monument as found, lowered monument, removed monument (explain)
- On 3-19-1990 placed a 2" X 48" brass capped monument
DATE

Monument Marked


SKETCH OF REFERENCE TIES
not to scale



SEC. 1



SEC. 12



bearings are true

All trees are scribed, painted with a 30d spike in side and USFS 54-3 tag.

Statement of evidence relative to this corner location is on back of page.

323151

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

William C. Ospe

Date 8/22/90 Registration No. 17767

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 3:10 P.M. on the 28 day of August A.D., 1990

County Recorder Claudine Kayler

By MS, Deputy

DOCUMENT NO. 323151

Statement of Evidence:

E23 North quarter corner section 12

1/4 Cor. 1 and 12 (N 1/4 Cor. Sec. 12)

- 1872 U.S. General Land Office survey set wood post for corner and the following references were noted:
W. Pine 10" S 48 degrees E, 50 Links (33.00 feet)
Spruce 12" N 52 degrees W, 15 Links (9.90 feet)
- 7-1-1964 USFS corner card states Morrison and Morgan, found blue line painted north and east from area, no post or BT's, they placed an approx. corner tag on a 2" Pincherry.
- 9-24-1969 Curt Krause, USFS, chained to area from Township road, found pine stumps in area, no evidence of corner.
- 11-9-1989 Personnel from Kovanen & Osufsen Inc. chained to area from Township road at 1330' enter spruce plantation, 2640 leave plantation, found nothing in search area. No topo calls in original notes. 1/4 cor. 40.27 ch (2657.82 feet)
- 3-19-1990 Personnel from Kovanen & Osufsen Inc. set a 2" x 48" brass capped monument by single proportion measurement and on line, between the Northeast corner of Section 12 and the reestablished Northwest corner of Section 12, then witnessed as follows:
Maple 7" S 37 degrees W, 56.98 feet
Spruce 6" N 23 degrees W, 33.49 feet
Spruce 5" N 02 degrees E, 19.19 feet
Set 8' long steel sign post with sign attached, East 1.5 feet
Set 8' long steel sign post with sign attached, North 3.3 feet

This position is not traceable to the original GLO corner, but accepted as corner for lack of further evidence.