

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 35, Township 143N, Range 26W, 5th P.M.

STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

- On _____ found a _____
DATE
- left monument as found, lowered monument, removed monument (explain)
- On 6-25-90 placed a 2 inch x 54 inch Brass capped monument
DATE

Monument marked

T143N, R26W
S26
N-1/4
S35
1990
RLS 17767

SKETCH OF REFERENCE TIES

Not to scale

Sec. 26

5 inch Maple
N 51° W 50.07 feet

○ ————— ■ Sign post 4.0 feet

7 inch Maple
S 60° W
39.60 feet

■ Sign post
3.4 feet

10 inch Aspen
S 28° E 22.40 feet

Sec. 35

All bearings true

All trees scribed, painted with a 30d spike, and USFS 54-3 tag.

Statement of evidence relative to this corner location is on back of page.

325151

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

William C. Dwyer

Date 11/14/90 Registration No. 17767

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 4:05 P. on the 21 day of November A.D., 1990

County Recorder Claudia Kaylor

By mj, Deputy

DOCUMENT NO. 325151

Statement of Evidence:

V19 North quarter corner section 35

1/4 Cor. 26 and 35 (N 1/4 Cor. Sec. 35)

- 1872 U.S. General Land Office survey set wood post for corner and the following references were noted:
Birch 7" S 52 degrees W, 8 Links (5.28 feet)
Birch 8" N 10 degrees E, 10 Links (6.60 feet)
- 1968 Curt Krause, USFS, chained to search area from section corner to west, no evidence of corner, or BT's found.
- 11-13-1989 Personnel from Kovanen & Osufsen Inc. chain to search area from section corner to east, found approximate corner tag at corner of clear cut, area has been logged and burned, no evidence of corner, or BT's found.
- 6-25-1990 Personnel from Kovanen & Osufsen Inc. set a 2" x 54" brass capped monument midway and on line between the reestablished NW corner of section 35 and the recovered NE corner of section 35. The following witnesses were established:
Maple 5" N 51 degrees W, 50.07 feet
Maple 7" S 60 degrees W, 39.60 feet
Aspen 10" S 28 degrees E, 22.40 feet
Set 8' long steel sign post with sign attached, East 4.0 feet
Set 8' long steel sign post with sign attached, South 3.4 feet

This position is not traceable to the original GLO corner, but accepted as corner for lack of further evidence.